

OPTIONAL INFORMATION	
Name of School:	Date of Inspection:
Vocational Program/Course/Room:	Signature of Inspector:

**POWERED LAWNMOWERS
SELF INSPECTION CHECKLIST**

Guidelines: This checklist covers the regulations issued by the U.S. Department of Labor - OSHA under the General Industry standard 29 CFR 1910.243(e) which was adopted by reference. It applies to walk-behind and riding rotary mowers. Selected design specifications required in 29 CFR 1910.243(e) have not been included as part of this checklist. Please consult the OSHA regulations for additional details in this area.

General Requirements

Please Circle

- | | | |
|----|--|------------|
| 1. | Are all power-driven chains, belts, and gears so positioned or otherwise guarded to prevent the operator's accidental contact during starting, mounting and operation? [29 CFR 1910.243(e)(1)(ii)] | Y N N/A DK |
| 2. | Is a shutoff device provided to stop operation of a motor or engine? [29 CFR 1910.243(e)(1)(iii)] | Y N N/A DK |
| | Note: This device shall require manual and intentional reactivation to restart the motor or engine. [29 CFR 1910.243(e)(1)(iii)] | |
| 3. | Are all positions of the operating controls clearly identified? [29 CFR 1910.243(e)(1)(iv)] | Y N N/A DK |

Comments/Corrective Action

**POWERED LAWNMOWERS
SELF INSPECTION CHECKLIST**

4. Are the words "**Caution. Be sure the operating control(s) is in neutral before starting the engine**" or similar wording clearly visible at an engine starting control point on self-propelled mowers? [29 CFR 1910.243(e)(1)(v)] Y N N/A DK

Walk-behind and Riding Rotary Mowers

5. Is the mower blade enclosed except on the bottom and the enclosure extended to or below the lowest cutting point of the blade in the lowest blade position? [29 CFR 1910.243(e)(2)(i)] Y N N/A DK
6. Do guards which must be removed to install a catcher assembly have warning instructions affixed to the mower near the opening stating that the mower shall not be used without either the catcher assembly or the guard in place? [29 CFR 1910.243(e)(2)(ii)] Y N N/A DK
7. Are openings in the blade enclosure, intended for discharge of grass, limited to a maximum vertical angle of the opening of 30 degrees measured from the lowest blade position? [29 CFR 1910.243(e)(2)(iii)] Y N N/A DK
8. Is the word "**Caution**" or stronger wording placed on the mower at or near the discharge opening? [29 CFR 1910.243(e)(2)(v)] Y N N/A DK
9. After declutching or shutting off the power, do the blades stop rotating from the manufacturer's maximum speed within 15 seconds? [29 CFR 1910.243(e)(2)(vii)] Y N N/A DK

Comments/Corrective Action

**POWERED LAWNMOWERS
SELF INSPECTION CHECKLIST**

Walk-behind Rotary Mowers

- | | | |
|-----|--|------------|
| 10. | Is the horizontal angle of the opening(s) in the blade enclosure intended for the discharge of grass directed so as to not contact the operator? [29 CFR 1910.243(e)(3)(i)] | Y N N/A DK |
| 11. | Does one of the following exist at all openings in the blade enclosure intended for the discharge of grass? [29 CFR 1910.243(e)(3)(ii)] | Y N N/A DK |
| | (a) A minimum unobstructed horizontal distance of 3 inches from the end of the discharge chute to the blade tip circle | |
| | (b) A rigid bar fastened across the discharge opening, secured to prevent removal without the use of tools. The bottom of the bar shall be no higher than the bottom edge of the blade enclosure. | |
| 12. | Does the highest point on the blade enclosure front, except discharge openings, not exceed 1-1/4 inches above the lowest cutting point of the blade in the lowest blade position? [29 CFR 1910.243(e)(3)(iii)] | Y N N/A DK |
| 13. | Is the mower handle fastened to the mower to prevent loss of control by unintentional uncoupling? [29 CFR 1910.243(e)(3)(iv)] | Y N N/A DK |
| 14. | Is a positive upstop or latch provided for the mower handle in the normal operating position? [29 CFR 1910.243(e)(3)(v)] | Y N N/A DK |

Note: The upstop shall not be subjected to unintentional disengagement during normal operation of the mower.

Comments/Corrective Action

**POWERED LAWNMOWERS
SELF INSPECTION CHECKLIST**

15. Do wheel drive disengaging controls, except deadman controls, move opposite to the direction of the vehicle motion in order to disengage the drive? [29 CFR 1910.243(e)(3)(vii)] Y N N/A DK

Note: Deadman controls shall automatically interrupt the power to a drive when the operator's activating force is removed, and may operate in any direction to disengage the drive.

Riding Rotary Mowers

16. Are openings placed so that grass or debris will not discharge directly toward any part of the operator's seat in the normal operating position? [29 CFR 1910.243(e)(4)(ii)] Y N N/A DK

17. Does one of the following exist at all openings in the blade enclosures intended for the discharge of grass? [29 CFR 1910.243(e)(4)(iii)] Y N N/A DK

(a) A minimum unobstructed horizontal distance of 6 inches from the end of the discharge chute to the blade tip circle

(b) A rigid bar fastened across the discharge opening, secured to prevent removal without the use of tools. The bottom of the bar shall be no higher than the bottom edge of the blade enclosure.

18. Are mowers provided with stops to prevent jackknifing or locking of the steering mechanisms? [29 CFR 1910.243(e)(4)(iv)] Y N N/A DK

Comments/Corrective Action

**POWERED LAWNMOWERS
SELF INSPECTION CHECKLIST**

- | | | |
|-----|--|------------|
| 19. | Are vehicle stopping means provided? [29 CFR 1910.243(e)(4)(v)] | Y N N/A DK |
| 20. | Do hand-operated wheel drive disengaging controls move opposite to the direction of the vehicle motion in order to disengage the drive? [29 CFR 1910.243(e)(4)(vi)] | Y N N/A DK |
| 21. | Do foot-operated wheel drive disengaging controls disengage the drive when depressed? [29 CFR 1910.243(e)(4)(vi)] | Y N N/A DK |
| 22. | Do deadman controls, both hand and foot operated, automatically interrupt power to the drive when the mower's actuating force is removed, and operate in any direction to disengage the drive? [29 CFR 1910.243(e)(4)(vi)] | Y N N/A DK |

Comments/Corrective Action

**POWERED LAWNMOWERS
SELF INSPECTION CHECKLIST**

Blank Page