


pen table=\\njdotprjwa\ssystem\njdotrws\projects\jdoteng\iploct\bia\roadway\Details.tbl

scale=30.0000000:1.0000000

date=11-APR-2018 09:07

ID=TP2VILL


BCD60-05-REVISED SECTION D-D & D'-D' DIM.
BCD70-02-NEW SHEET





NOTES:

1. SEE CD-609-13 FOR ADDITIONAL NOTES AND DETAILS.
2. THE MINIMUM TAPER LENGTH IS BASED ON PARAPET HEIGHT. THE TAPER MUST BE 5:1 OR FLATTER WITH 8:1 DESIRABLE. SEE BRIDGE PLANS FOR TAPER LENGTH.
3. REINFORCEMENT STEEL IS IN METRIC UNITS.
4. FOR ADDITIONAL PARAPET DETAILS & DIMENSIONS, REFER TO BCD-507-9.


PLAN



ELEVATION



SECTION: E-E



BEAM GUIDE RAIL ATTACHMENTS

N.T.S.

CD-609-15A

NEW JERSEY DEPARTMENT OF TRANSPORTATION

CONSTRUCTION DETAILS

GUIDE RAIL ATTACHMENT - NEW CONSTRUCTION - DESIGN SPEED 45 MPH OR LESS (MASH TL-2) F SHAPE BARRIER PARAPET (NO ROADWAY CURBING ON APPROACH)

CD-609-15A.1

76A
164