







pen table=\\NDOT\PRGWS\Vegsystem\NDOT\TWS\Projects\NDOT\TWS\Project\TBLA\Roadway\Details\11x17.tbl
scale=63.9890711.000000
date=19-JUL-2017 14:36
ID=TP2VTL

BC07D-02-NEW SHEET



NOTES:

1. SEE CD-609-13 FOR ADDITIONAL NOTES AND DETAILS.
2. THE MINIMUM TAPER LENGTH IS BASED ON PARAPET HEIGHT. THE TAPER MUST BE 5:1 OR FLATTER WITH 8:1 DESIRABLE. SEE BRIDGE PLANS FOR TAPER LENGTH.
3. REINFORCEMENT STEEL IS IN METRIC UNITS.
4. FOR ADDITIONAL PARAPET DETAILS & DIMENSIONS, REFER TO BCD-509-6.



BEAM GUIDE RAIL ATTACHMENTS

N.T.S.

CD-609-16A

NEW JERSEY DEPARTMENT OF TRANSPORTATION

CONSTRUCTION DETAILS

**GUIDE RAIL ATTACHMENT - NEW CONSTRUCTION - DESIGN SPEED 45 MPH OR LESS (MASH TL-2)
SIDEWALK WITH ONE RAIL STEEL BRIDGE RAILING PARAPET**

CD-609-16A.1