

OVERLAPPING DUAL FACED MEDIAN BEAM GUIDE RAIL

NOTES:

1. ATTACH AN END SECTION (ROUNDED) WHERE DUAL-FACED BEAM GUIDE RAIL TERMINATES. SEE CD-609-2.
2. WHERE CLEARANCE FROM THE OBSTRUCTION TO THE FACE OF RAIL IS LESS THAN 4', REDUCED POST SPACING IS REQUIRED. SEE CD-609-8.
3. EXTEND DUAL FACED GUIDE RAIL A MINIMUM OF ONE 6'-3" SPACE (TWO POSTS) BEYOND A 45 DEGREE LINE EXTENDED FROM THE LAST POST OF THE BEAM GUIDE RAIL ANCHORAGE.
4. LOCATION OF CONCRETE PAD AS SHOWN ON THE PLANS.



OVERLAPPING DUAL FACED MEDIAN BEAM GUIDE RAIL WITH CONCRETE PAD



17' X 17' CONCRETE PAD



SECTION A–A

MEDIAN GUIDE RAIL TREATMENTS

N.T.S.

CD-609-7B

NEW JERSEY DEPARTMENT OF TRANSPORTATION

CONSTRUCTION DETAILS

CD-609-7B.1

68B
164

ID=TP2VLL date=19-JUL-2017 14:35 scale=64.069920:1.000000 pen table=\\NJDOTFRJWS\Projects\NJDOTEng\pjoi\TBLs\Roadway\Details_22x17.tbl
BDCOTD-02-NEW SHEET
file=