

MEDIAN GUIDE RAIL WITH TELESCOPING GUIDE RAIL END TERMINAL



SECTION A–A

NOTES:

1. 10H:1V OR FLATTER SLOPES TO BEGIN 100' IN ADVANCE OF THE TELESCOPING GUIDE RAIL END TERMINAL.
2. WHERE THE DISTANCE FROM THE FACE OF RAIL TO THE OBSTRUCTION IS LESS THAN 4', REDUCED POST SPACING IS REQUIRED. SEE CD-609-8.
3. A MINIMUM OF ONE 6'-3" TANGENT SPACE IS REQUIRED BEYOND THE OBSTRUCTION BEFORE BEGINNING A FLARE.
4. LENGTH OF TELESCOPING GUIDE RAIL END TERMINAL AS PER MANUFACTURER. SEE QUALIFIED PRODUCTS LIST.



SECTION B–B



TELESCOPING GUIDE RAIL END TERMINAL CONNECTION TO DUAL FACED BEAM GUIDE RAIL

TELESCOPING GUIDE RAIL END TERMINAL

CD-609-7.1



DUAL FACED MEDIAN GUIDE RAIL AND TANGENT GUIDE RAIL TERMINAL



SECTION C–C

CD-609-7.2

MEDIAN GUIDE RAIL TREATMENTS

N.T.S.

CD-609-7

NEW JERSEY DEPARTMENT OF TRANSPORTATION

CONSTRUCTION DETAILS

BDC160-07-DUAL FACED DETAIL TEXT REVISED
BDC170-04-REVISIONS TO CD-609-7
BDC180-04-ORIGINAL SHEET