


pen table=\\jdotprjw\ssystem\jdotprjw\projects\jdoteng\ipdot\table\roadway\Details.tbl

scale=30.0000000:1.0000000


date=11-APR-2018 14:02

ID=TP2VILL

BCD8D-05-REVISED SECTION D-D & D'-D' DIM.
BCD7D-02-REVISIONS TO CD-609-14
BCD6D-01-ORIGINAL SHEET




PLAN




ELEVATION

NOTES:


1. SEE CD-609-13 FOR ADDITIONAL NOTES AND DETAILS.
2. THE MINIMUM TAPER LENGTH IS BASED ON PARAPET HEIGHT. THE TAPER MUST BE 5:1 OR FLATTER WITH 8:1 DESIRABLE. SEE BRIDGE PLANS FOR TAPER LENGTH.
3. REINFORCEMENT STEEL IS IN METRIC UNITS.
4. FOR ADDITIONAL PARAPET DETAILS & DIMENSIONS, REFER TO BCD-507-9.




SECTION: A-A
(ON SPAN)




SECTION: B-B
(ON SPAN)




SECTION: C-C
(ON SPAN)



SECTION: D-D
(ON SPAN)



SECTION: E-E



INTERIOR ELEVATION
PARAPET REINFORCEMENT
TYPE A ATTACHMENT

BEAM GUIDE RAIL
ATTACHMENTS

N.T.S.

CD-609-14

NEW JERSEY DEPARTMENT OF TRANSPORTATION

CONSTRUCTION DETAILS

GUIDE RAIL ATTACHMENT - NEW CONSTRUCTION - DESIGN SPEED GREATER THAN 45 MPH (MASH TL-3)
F SHAPE BARRIER PARAPET (NO ROADWAY CURBING ON APPROACH)

CD-609-14.1