


pen table=\\\\njdotprjw\\vssystem\\njdotwvs\\projects\\njdoteng\\ipilot\\tbla\\roadway\\Details.tbl
scale=30.0000000:1.0000000
date=01-APR-2015 13:48
ID=TP2TANG
BDCHD-04- TREATMENT & TRANSITION
BDC07D-01- ORIGINAL SHEET




NOTE:
ESCAPE RAMPS MUST BE CONSTRUCTED AND MAINTAINED DURING NON-WORKING HOURS WHERE A VERTICAL DROP GREATER THAN 2 INCHES EXISTS ADJACENT TO TRAVELED LANE.

ESCAPE RAMP DETAIL

REGULATORY APPROACH SPEED OF TRAFFIC MILES/HOUR	RECOMMENDED SIGHT DISTANCE TO BEGINNING OF CHANNELIZING TAPERS		
	DESIRABLE		MINIMUM
	RURAL FEET	URBAN FEET	RURAL AND URBAN FEET
25	375	525	150
30	450	625	200
35	525	725	250
40	600	825	325
45	675	925	400
50	750	1025	475
55	875	1150	550
60	1000	1275	650
65	1050		725

- NOTES:**
- AVOIDANCE MANEUVER IS FOR A SPEED, PATH, AND/OR DIRECTION CHANGE PRIOR TO THE BEGINNING OF CHANNELIZING TAPERS.
 - RECOMMENDED DISTANCES BETWEEN TWO SEPARATE LANE CLOSURES ARE DOUBLE THE VALUES SHOWN ABOVE.
 - RURAL AND URBAN ROAD DESIGNATIONS ARE AS DEFINED IN THE NJDOT STATE HIGHWAY STRAIGHT LINE DIAGRAMS.
 - PROVIDE DESIRABLE VALUES WHEREVER POSSIBLE. IF IT IS NOT FEASIBLE OR PRACTICAL TO PROVIDE DESIRABLE VALUES BECAUSE OF HORIZONTAL OR VERTICAL CURVATURE OR IF RELOCATION OF THE TAPER IS NOT POSSIBLE, THEN MINIMUM VALUES CAN BE APPLIED. WHEN MINIMUM VALUES ARE USED, PAY SPECIAL ATTENTION TO THE USE OF SUITABLE TRAFFIC CONTROL DEVICES WHEN PROVIDING ADVANCED WARNING OF THE CONDITIONS THAT ARE LIKELY TO BE ENCOUNTERED.
 - LOCATE TAPERS TO MAXIMIZE THE VISIBILITY OF THEIR TOTAL LENGTH.




STAGE	LOCATION	CONNECTION TYPE
	RTE. STA. TO STA.	

CONNECTION TYPE	MIN. OFFSET	MAX. OVERHANG	CLEAR AREA
B	12"	16"	28"

OPTIONAL CONNECTION TYPE B TREATMENT AT VERTICAL DROP OFF

RECOMMENDED TAPER LENGTH AND SPACING FOR CHANNELIZING TAPERS					RECOMMENDED SPACING ALONG TANGENTS	
REGULATORY APPROACH SPEED OF TRAFFIC MILES/HOUR	MINIMUM TAPER RATIO IN LENGTH PER FOOT OF WIDTH	MINIMUM TAPER LENGTH L - FOR LANE WIDTHS			MAXIMUM DEVICE (B) SPACING ALONG TAPERS IN FEET	MAXIMUM DEVICE (D) SPACING ALONG TANGENTS IN FEET
25	10.5:1	10'	11'	12'	25	50
30	15:1	150	165	180	30	60
35	20.5:1	205	225	245	35	70
40	27:1	270	300	325	40	80
45	45:1	450	495	540	45	90
50	50:1	500	550	600	50	100
55	55:1	550	605	660	55	110
60	60:1	600	660	720	60	120
65	65:1	650	715	780	65	130

NOTE:
THE MAXIMUM DEVICE SPACING ALONG CURVES IS DEFINED FOR TAPERS (B) IN THE ABOVE TABLE.



- NOTES:**
- CHANGES TO THE PROPOSED CONNECTION TYPE AT ANY LOCATION MUST BE APPROVED BY THE DEPARTMENT.
 - NO ROADWAY DROP OFFS, OBSTRUCTIONS, STORAGE OF MATERIALS OR WORK WILL BE PERMITTED IN THE CLEAR AREA UNLESS APPROVED BY THE RE. EXCEPT ROADWAY DROP OFFS ARE PERMITTED ONLY WHEN USING THE OPTIONAL CONNECTION TYPE B TREATMENT AT VERTICAL DROP OFF.

STAGE	LOCATION	CONNECTION TYPE
	RTE. STA. TO STA.	


CONNECTION TYPE	CLEAR AREA
A	41 INCHES
B	28 INCHES
C	11 INCHES

CONSTRUCTION BARRIER CURB CONNECTION TYPE AND CLEAR AREA


NOTE TO DESIGNER:

THIS SHEET REQUIRES DESIGN SPECIFIC INFORMATION TO BE ADDED AND INCLUDED IN THE CONTRACT PLANS.

REMOVE THIS NOTE AFTER DESIGN SPECIFIC INFORMATION IS ADDED.



CONNECTION TYPE B TRANSITION



CONNECTION TYPE C TRANSITION

N.T.S.

TCD-2
NEW JERSEY DEPARTMENT OF TRANSPORTATION

TRAFFIC CONTROL DETAILS