

BDC03D-06 - CD-607-2.9 & 2.10 HAVE BEEN
RELOCATED FROM CD-607-1.1 & CD-607-1.2
BDC03D-06 - CD-607-2.1 CD-607-2.2 & CD-607-2.3
BDC00D-1 - ORIGINAL SHEET

CD-607-2.1

RESURFACING OF EXISTING HMA DRIVEWAY
(WITH DEPRESSED CURB)

TYPE A

CD-607-2.2

RESURFACING OF EXISTING HMA DRIVEWAY
(WITHOUT DEPRESSED CURB)

TYPE B

CD-607-2.3

GENERAL NOTES

1. ALL MATERIAL, REPAIR STRIPS AND EXCAVATION FOR DRIVEWAY CONSTRUCTION TO BE INCLUDED IN THE BID PRICE FOR HMA DRIVEWAY, CONCRETE DRIVEWAY OR CONCRETE CURB.
2. HMA DRIVEWAY SURFACE COURSE, TOP LAYER AND BOTTOM LAYER SHALL BE MIX 1-5, OR THE SURFACE COURSE MIX TO BE USED ON THE PROJECT.
3. LENGTH OF DRIVEWAY WORK SHALL BE 5 FEET UNLESS OTHERWISE SHOWN ON PLANS OR AS DIRECTED.
4. MAINTAIN EXISTING DIRECTION OF FLOW ON DRIVEWAY.
5. DENSE GRADED AGGREGATE BASE COURSE SHALL BE USED TO PROVIDE TEMPORARY ACCESS DURING DRIVEWAY CONSTRUCTION.
6. GRANULAR MATERIAL FROM THE PROJECT OR SOIL AGGREGATE AS DIRECTED.
7. NO BASE COURSE IS REQUIRED FOR DRIVEWAY.

CD-607-2.4

CONSTRUCTION OF HMA DRIVEWAY
OR CONVERSION OF EXISTING GRAVEL DRIVEWAY
(WITH DEPRESSED CURB)

TYPE C

CD-607-2.5

CONSTRUCTION OF HMA DRIVEWAY
OR CONVERSION OF EXISTING GRAVEL DRIVEWAY
(WITHOUT DEPRESSED CURB)

TYPE D

CD-607-2.6

RECONSTRUCTION OF CONCRETE DRIVEWAY
(WITH DEPRESSED CURB)

TYPE E

CD-607-2.7

RECONSTRUCTION OF CONCRETE DRIVEWAY
(WITHOUT DEPRESSED CURB)

TYPE F

CD-607-2.8

TYPICAL DRIVEWAY TREATMENT

PLAN VIEW

CD-607-2.9

CONCRETE SIDEWALK, 4\"/>

CD-607-2.10

HMA SIDEWALK, 5 1/2\"/>

NEW JERSEY DEPARTMENT OF TRANSPORTATION

CD-607-2

CONSTRUCTION DETAILS

38129