STATE	FEDERAL PROJECT NO.	SHEET	TOTAL SHEETS
N. J.			

STRUCTURE NO.



PLAN AT SIDEWALK

PLAN AT SPLIT MEDIAN BARRIER

PLAN AT ALTERNATE SIDEWALK

NOTE:
** SEE NOTE ON SHEET 1.



SECTION AT SIDEWALK

NOTE: SECTION IS SIMILAR FOR RAISED SIDEWALK.

SECTION AT SPLIT MEDIAN BARRIER

NOTE: FOR MEDIAN BARRIER NOT SPLIT, USE ONE PIECE ½" BENT SLIDING PLATE. STEEL EXTRUSION IS SHOWN FOR 90° SKEW. DETAIL STEEL EXTRUSION AS REQUIRED FOR SKEWS LESS THAN 90°.

SECTION AT ALTERNATE SIDEWALK

NOTES:

1. MAXIMUM DISTANCE FROM EDGE OF EXTENSION OR BEND TO FIRST STUD IS 3".
2. FOR STEEL EXTRUSION DETAIL, SEE SHEET 2.
3. FOR SECTION B-B, SEE SHEET 5.
4. DRAIN RUNOFF WITH CURB DRAINS THROUGH CONCRETE BARRIER OR WITH SCUPPERS IN SIDEWALK SLAB. WHERE CURB DRAINS ARE USED, SET SIDEWALK ELEVATION AT REAR FACE OF BARRIER 1" ABOVE GUTTERLINE ELEVATION.

CONTROL SECTION		JOB NO.	
DES. BY		CHK. BY	
DWN. BY			
EST. BY		CHK. BY	
SPECS. BY			

IN CHARGE OF

STANDARD DRAWING PLATE 2.7-4

NEW JERSEY DEPARTMENT OF TRANSPORTATION
BUREAU OF STRUCTURAL ENGINEERING

STRIP SEAL EXPANSION JOINT ASSEMBLY FOR PRESTRESSED CONCRETE & STEEL BEAM BRIDGES

ROUTE : SECTION :

MUNICIPALITY COUNTY

SCALE : NONE

BRIDGE SHEET NO. OF