Division of Solid & Hazardous Waste P.O. Box 421 Trenton, New Jersey 08625-0421 Phone# 609-292-9880 Fax# 609-633-9839

Hazardous Waste Facility Permit

Under the provisions of N.J.S.A. 13:1E-1 <u>et seq</u>. known as the Solid Waste Management Act, this permit is hereby issued to:

Cycle Chem Inc. 217 South First Street Elizabeth NJ 07206

For the Purpose of Operating a:	Hazardous Waste Storage, Treatment,
	and Transfer Facility
On Block No.:	2
Lot Nos.:	865, part of 74
In the Municipality of:	Elizabeth
County:	Union
Under Facility Permit No.:	2004E2HP08
EPA ID No.:	NJD 002 200 046

This permit is subject to compliance with all conditions specified herein and all regulations promulgated by the Department of Environmental Protection.

This permit shall not prejudice any claim the State may have to riparian land, nor does it allow the permittee to fill or alter or allow to be filled or altered in any way, lands that are deemed to be riparian, wetlands, stream encroachment areas or flood plains, or that are within the Coastal Area Facility Review Act (CAFRA) zone or are subject to the Pinelands Protection Act of 1979, nor shall it allow the discharge of pollutants to waters of this State without prior acquisition of the necessary grants, permits, or approvals from the Department of Environmental Protection or the U.S. Environmental Protection Agency.

October 15, 1996	Signed by John A. Castner, P.E., P.P., Assistant Director
	John A. Castner, P.E., P.P.
	Assistant Director
December 3, 1997	Division of Solid & Hazardous Waste
Reissuance Date	
January 3, 1998	
Effective Date	
May 5, 1998	
Modification Date	
November 15, 2006 Expiration Date	

Table of Contents

Item	Page
Scope of Permit Description of Hazardous Waste Activities Summary of Permit Compliance Conditions	3 4 4
Section I - General Conditions Applicable to all Permits	
 Duty to Comply Duty to Reapply Need to Halt or Reduce Activity Not a Defense Need to Mitigate Proper Operation and Maintenance Permit Actions Property Rights Duty to Provide Information Inspection and Entry Monitoring and Records Signatory Requirement Reporting Requirements 	5 5 5 5 6 6 6 6 6 7 7
Section II - General Conditions Applicable to Cycle Chem Inc.	
 Permit Modification or Revocation and Reissuance Personnel Training Preparedness and Prevention Contingency Plan Security Termination of a Permit Operating Record Permit Limitations Financial Requirements Compliance with Other State Regulations and Statutes Submission of Documents Required by Permit Conditions Referenced Permit Application Documents 	11 11 12 13 14 15 15 15 16 16 16
Section III - Specific Conditions Applicable to Cycle Chem Inc.	
 Authorized Activities Authorized Wastes Waste Analysis and Quality Assurance Requirements Inspection Requirements Closure of Hazardous Waste Management Units Construction/Installation Requirements Additional Part B Permit Application Requirements 	20 28 30 35 39 41 42

Page 3 of 42 Cycle Chem, Inc. HWF Permit

Scope of Permit

The hazardous waste rules at N.J.A.C. 7:26G were adopted by the New Jersey Department of Environmental Protection on October 21, 1996. By this adoption, the Department "incorporated by reference" (with limited exception) the July 1, 1993 version of the Federal hazardous waste regulations found at Parts 124, 260-266, 268 and 270, Title 40 of the Code of Federal Regulations (C.F.R.). Those provisions of the Federal regulations which were not incorporated by reference are listed in the State regulatory adoption. Additional changes to the New Jersey hazardous waste rules will be necessary to address Federal regulations adopted subsequent to July 1, 1993. The Department anticipates addressing these subsequent Federal regulations in a regulatory adoption sometime in 1997. At that time, the Department will adopt amendments to N.J.A.C. 7:26G incorporate by reference those changes to the Federal to regulations that have been made since July 1, 1993, and a prospective incorporation by reference which will incorporate all future amendments and supplements to the Federal regulations automatically. Within 180 days of the effective date of these amendments to N.J.A.C. 7:26G, the Department will initiate a modification of this permit to incorporate such provisions as are made necessary by the newly adopted rules.

The conditions of this permit are based on the New Jersey hazardous waste regulations at N.J.A.C. 7:26G and on the permit application submitted by the permittee. In order to eliminate confusion, and to clearly describe the precise obligations which are imposed upon the permittee, only the specific Federal regulatory citations as of July 1, 1993 are listed in the conditions of this permit. For the applicable State regulatory citations, refer to N.J.A.C. 7:26G.

This permit, along with the referenced permit application documents herein specified, shall constitute the sole Hazardous Waste Facility Permit for the operation of a hazardous waste storage, treatment, and transfer facility by Cycle Chem Inc. in Elizabeth, Union County, New Jersey. Any registration, approval, or permit previously issued by the Division of Solid & Hazardous Waste or its predecessor agencies to authorize hazardous waste operations at the subject facility is hereby superseded. The permittee need not comply with the conditions of this permit to the extent and for the duration such non-compliance is authorized by an emergency permit $(40 \text{ C.F.R.} \rightarrow 270.61).$

Section I of this permit contains the general conditions applicable to all hazardous waste facilities. Section II of this permit contains general conditions applicable to Cycle Chem Inc.. Section III of this permit contains specific conditions applicable to the hazardous waste management practices at the Cycle Chem Inc. facility. Page 4 of 42 Cycle Chem, Inc. HWF Permit

Description of Hazardous Waste Activities

The permittee operates a facility involved in the commercial storage, treatment, and transfer of hazardous and non-hazardous waste in containers and tanks. The permittee is authorized to accept containerized and bulk liquids, semi-liquids, sludges, solids, and containerized low pressure gases and aerosols at the facility for storage and various types of physical and chemical treatment as authorized by this permit prior to shipment to authorized off-site facilities. The permittee is authorized to store and treat a maximum of two hundred forty-nine thousand, nine hundred ninety-nine (249,999) gallons in containers and tanks at the site. There is no disposal of hazardous waste at the Cycle Chem facility.

Summary of Permit Compliance Conditions

The permittee shall conduct periodic assessments of all storage tanks and ancillary equipment in accordance with Condition 4(b)2 of Section III of this permit, until such time as all tank system secondary containment units meet the requirements of 40 C.F.R. $_{2}$ 264.193.

The permittee shall submit plans, specifications, and engineering designs, as applicable, and quarterly progress reports for the upgrade of tank secondary containment units to meet the requirements of 40 C.F.R. \rightarrow 264.193, in accordance with Condition 6 of Section III of this permit.

The permittee shall submit additional permit application information in accordance with Condition 7 of Section III of this permit to conform to the regulatory requirements of 40 C.F.R. $_{33}$ 260 through 270.

Section I

General Conditions Applicable to All Permits (40 C.F.R. 3 270.30)

1. Duty to Comply

The permittee must comply with all conditions of this permit, except that the permittee need not comply with the conditions of this permit to the extent and for the duration such noncompliance is authorized in an emergency permit. (See 40 C.F.R. \rightarrow 270.61). Any permit noncompliance, except under the terms of an emergency permit, constitutes a violation of the appropriate Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application.

2. Duty to Reapply

- (a) If the permittee wishes to continue an activity regulated by this permit after the expiration date of this permit, the permittee must apply for and obtain a new permit.
- (b) A complete application for a new permit shall be submitted at least one hundred eighty (180) days prior to the expiration date of this permit.

3. Need to Halt or Reduce Activity Not a Defense

It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

4. Need to Mitigate

In the event of noncompliance with the permit, the permittee shall take all reasonable steps to minimize releases to the environment, and shall carry out such measures as are reasonable to prevent significant adverse impacts on human health or the environment.

5. Proper Operation and Maintenance

The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance includes effective performance, adequate funding, adequate operator staffing and training, and adequate laboratory and process controls, including appropriate quality assurance procedures. This provision requires the operation of back-up or auxiliary facilities or similar systems only when necessary to achieve Page 6 of 42 Cycle Chem, Inc. HWF Permit

compliance with the conditions of the permit.

6. Permit Actions

This permit may be modified, revoked and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance, does not stay any permit condition.

7. Property Rights

The permit does not convey any property rights of any sort, or any exclusive privilege.

8. Duty to Provide Information

The permittee shall furnish to the Department, within a reasonable time, any relevant information which the Department may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The permittee shall also furnish to the Department, upon request, copies of records required to be kept by this permit.

9. Inspection and Entry

The permittee shall allow an authorized representative of the Department upon the presentation of credentials and other documents as may be required by law to:

- (a) Enter at reasonable times upon the permittee's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit; and
- (d) Sample or monitor at reasonable times, for the purposes of assuring permit compliance or as otherwise authorized by RCRA, any substances or parameters at any location.

10. Monitoring and Records

- (a) Samples and measurements taken for the purpose of monitoring shall be representative of the monitored activity.
- (b) The permittee shall retain records of all monitoring information, including all calibration and maintenance

Page 7 of 42 Cycle Chem, Inc. HWF Permit

records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, the certification required by 40 C.F.R. \rightarrow 264.73(b)(9) of this chapter, and records of all data used to complete the application for this permit, for a period of at least 3 years from the date of the sample, measurement, report, certification, or application. This period may be extended by request of the Department at any time. The permittee shall maintain records from all ground-water monitoring wells and associated ground-water surface elevations, for the active life of the facility, and for disposal facilities for the post-closure care period as well.

- (c) Records for monitoring information shall include:
 - (1) The date, exact place, and time of sampling or measurements;
 - (2) The individual(s) who performed the sampling or measurements;
 - (3) The date(s) analyses were performed;
 - (4) The individual(s) who performed the analyses;
 - (5) The analytical techniques or methods used; and
 - (6) The results of such analyses.

11. Signatory Requirements

All applications, reports, or information submitted to the Department shall be signed and certified. (see 40 C.F.R.) 270.11).

12. Reporting Requirements

(a) Planned Changes

The permittee shall give notice to the Department as soon as possible of any planned physical alterations or additions to the permitted facility.

(b) Anticipated Noncompliance

(1) The permittee shall give advance notice to the Department of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements. For a new facility, the permittee may not treat, store, or dispose of hazardous waste; and for a facility being modified, the permittee may not treat, store, or dispose of hazardous waste in the modified portion of the facility except as provided in Page 8 of 42 Cycle Chem, Inc. HWF Permit

40 C.F.R. 3 270.42, until:

- (i) The permittee has submitted to the Department by certified mail or hand delivery a letter signed by the permittee and a registered professional engineer stating that the facility has been constructed or modified in compliance with the permit; and
- (ii) (A) The Department has inspected the modified or newly constructed facility and finds it is in compliance with the conditions of the permit; or
 - (B) If, within 15 days of the date of submission of the letter in paragraph 12(b)1i of this section, the permittee has not received notice from the Department of his or her intent to inspect, prior inspection is waived and the permittee may commence treatment, storage, or disposal of hazardous waste.
- (c) Transfers

This permit is not transferable to any person except after notice to the Department. The Department may require modification or revocation and reissuance of the permit to change the name of the permittee and incorporate such other requirements as may be necessary under RCRA. (See 40 C.F.R. \rightarrow 270.40).

(d) Monitoring Reports

Monitoring results shall be reported at the intervals specified elsewhere in this permit.

(e) Compliance Schedules

Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule of this permit shall be submitted no later than 14 days following each schedule date.

(f) Twenty-four Hour Reporting

- (1) The permittee shall report any noncompliance which may endanger health or the environment orally within 24 hours from the time the permittee becomes aware of the circumstances, including:
 - (i) Information concerning the release of any hazardous waste that may cause an endangerment to public drinking water supplies.

Page 9 of 42 Cycle Chem, Inc. HWF Permit

- (ii) Any information of a release or discharge of hazardous waste or of a fire or explosion from the HWM facility, which could threaten the environment or human health outside the facility.
- (2) The description of the occurrence and its cause shall include:
 - (i) Name, address, and telephone number of the owner or operator;
 - (ii) Name, address, and telephone number of the facility;
 - (iii) Date, time, and type of incident;
 - (iv) Name and quantity of material(s) involved;
 - (v) The extent of injuries, if any;
 - (vi) An assessment of actual or potential hazards to the environment and human health outside the facility, where this is applicable; and
 - (vii) Estimated quantity and disposition of recovered material that resulted from the incident.
- A written submission shall also be provided within 5 (3) days of the time the permittee becomes aware of the circumstances. The written submission shall contain a description of the noncompliance and its cause; the period of noncompliance including exact dates and times, and if the noncompliance has not been corrected, the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance. The Department may waive the five day written notice requirement in favor of a written report within fifteen days.
- (4) Oral Notification shall be provided to the NJDEP Hotline at (609) 292-7172. Written notification shall be provided to the Bureau of Hazardous Waste and Transfer Facilities and the Bureau of Hazardous Waste Compliance and Enforcement at the addresses provided in Condition 11 of Section II of this permit.
- (g) Manifest Discrepancy Report

If a significant discrepancy in a manifest is discovered, the permittee must attempt to reconcile the discrepancy. If not resolved within fifteen days, the permittee must submit a letter report, including a copy of the manifest, Page 10 of 42 Cycle Chem, Inc. HWF Permit

to the Department. (See 40 C.F.R >264.72.)

(h) Unmanifested Waste Report

This report must be submitted to the Department within 15 days of receipt of unmanifested waste. (See 40 C.F.R. $_{2}264.76.$)

(i) Biennial Report

A biennial report must be submitted covering facility activities during odd numbered calendar years. (See 40 C.F.R. \rightarrow 264.75.)

(j) Other Noncompliance

The permittee shall report all instances of noncompliance not reported under paragraphs (d), (e) and (f) of this condition, at the time monitoring reports are submitted. The reports shall contain the information listed in paragraph (f) of this condition.

(k) Other Information

Where the permittee becomes aware that it failed to submit any relevant facts in a permit application, or submitted incorrect information in a permit application or in any report to the Department, it shall promptly submit such facts or information.

End of Section I

Page 11 of 42 Cycle Chem, Inc. HWF Permit

Section II

General Conditions Applicable to Cycle Chem Inc.

1. Permit Modification or Revocation and Reissuance

Cause for, and procedures of, modification, or revocation and reissuance of this permit shall be as provided under 40 C.F.R. **3** 270.41.

- 2. Personnel Training (40 C.F.R.) 264.16)
 - (a) Facility personnel shall successfully complete a program of classroom instruction or on-the-job training that teaches them to perform their duties in a way that insures the facility's compliance with the requirements of 40 C.F.R. 3 264.16, as stated in the facility's Part B permit application, and as referenced in Condition 12(b) of Section II of this permit. New employees shall be trained within six (6) months of the date of employment.
 - (b) The training program shall be maintained with records and documentation describing the type and amount of both introductory and continuing training that has been and will be given to each person engaged in hazardous waste management at the facility.
 - (c) The permittee shall keep the training records on current personnel until closure of the facility; training records on former employees shall be kept for at least three (3) years from the date the employee last worked at the facility. Personnel training records may accompany personnel transferred within the same company.
- 3. Preparedness and Prevention (40 C.F.R. 3264.30 through 3264.37) The facility shall be designed, constructed, maintained and operated to minimize the possibility of fire, explosion, or any unplanned sudden or non-sudden release of hazardous waste or hazardous waste constituents to the air, soil, surface water or groundwater which could threaten human health or the environment.
 - (a) The facility shall be equipped with emergency equipment, including but not limited to:
 - (1) An internal communications or alarm system capable of providing immediate emergency instruction (voice or signal) to facility personnel;
 - (2) A device, such as a telephone (immediately available at the scene of operations) or a hand-held two-way radio, capable of summoning emergency assistance from local police departments, fire departments, or State or local emergency response teams;

- (3) Portable fire extinguisher, fire control equipment, spill control equipment, and decontamination equipment; and
- (4) Water at adequate volume and pressure to supply water hose streams, or foam producing equipment, or automatic sprinklers, or water spray systems.
- (b) All facility communications or alarm systems, fire protection equipment, spill control equipment, and decontamination equipment, where required, shall be tested and maintained as necessary to assure its proper operation in time of emergency.

4. Contingency Plan (40 C.F.R.) 264.50 through) 264.56)

- (a) The provisions of the Contingency Plan included in the Part B permit application plus all amendments, revisions and modifications thereof subsequently submitted for review and accepted by the Department, and as referenced in Condition 12(b) of Section II of this permit, shall be carried out immediately whenever there is a fire, explosion or release of hazardous waste constituents which could threaten human health or the environment.
- (b) When an emergency coordinator determines that the facility has had a discharge, fire, or explosion which could threaten human health or the environment outside the facility, the emergency coordinator shall immediately notify the local Fire Department and local Police Department if an assessment indicates that evacuation of local areas may be advisable. The emergency coordinator shall be available to help officials decide if local areas should be evacuated. The telephone numbers are:

Fire Department: (908) 820-2800 or 911

Police Department: (908) 558-2111 or 911

(c) (1) If the facility has a discharge, fire, or explosion which could threaten human health or the environment, the following shall be notified immediately:

> New Jersey Department of Environmental Protection Communication Center/Trenton Dispatch Bureau of Communication and Support Services Trenton, NJ 08625 Telephone (609) 292-7172 (24 Hours)

(2) Additionally, if the emergency coordinator determines that the facility has had a discharge, fire, or explosion which could threaten human health or the environment outside the facility, the

Page 13 of 42 Cycle Chem, Inc. HWF Permit

emergency coordinator shall immediately notify:

National Response Center 2100 Second Street, SW Washington, D.C. 20593 Telephone 1-800-424-8802 (24 Hours)

- (d) If the emergency coordinator determines that the facility has had a discharge, fire, or explosion which would threaten human health or the environment, the emergency coordinator shall immediately notify the agencies listed in Condition 4(c) above. When notifying these agencies, the coordinator shall report the type of substance and the estimated quantity discharged, if known; the location of the discharge; actions the person reporting the discharge proposes to take to contain, clean up and remove the substance if any and any other information concerning the discharge which the Department may request at the time of notification.
- (e) The owner or operator shall note in the operating record the time, date, and details of any incident that requires implementing the contingency plan. Within 15 days after the incident, the owner or operator shall submit a written report on the incident to the Department. The report shall include, but not be limited to:
 - (1) Name, address, and telephone number of the owner or operator;
 - (2) Name, address, and telephone number of the facility;
 - (3) Date, time, and type of incident;
 - (4) Name and quantity of material(s) involved;
 - (5) The extent of injuries, if any;
 - (6) An assessment of actual or potential hazards to human health or the environment, where this is applicable; and
 - (7) An estimated quantity and disposition of recovered material that resulted from the incident.

5. Security (40 C.F.R.) 264.14)

- (a) The permittee must maintain the security procedures as described in the facility's Part B permit application plus all amendments, revisions and modifications thereof subsequently submitted for review and accepted by the Department, and as referenced in Condition 12(a) of Section II of this permit.
- (b) The permittee shall prevent the unknowing entry, and minimize the possibility for the unauthorized entry, of

Page 14 of 42 Cycle Chem, Inc. HWF Permit

persons or livestock onto the active portion of the facility.

- (1) A facility shall have:
 - (i) A 24-hour surveillance system which continuously monitors and controls entry onto the active portion of the facility; or
 - (ii) An artificial or natural barrier, which completely surrounds the active portion of the facility; and a means to control entry, at all times, through the gates or other entrances to the active portion of the facility.
- (2) The requirements of paragraph (b)1 are satisfied if the hazardous waste storage, treatment or disposal site is located in a facility which itself has a surveillance system, or a barrier and a means to control entry, which complies with the requirements of subparagraph (b)1i or (b)1ii.
- The owner or operator shall post a sign with the (3) legend, "Danger - Unauthorized Personnel Keep Out", at each entrance to the active portion of a facility, and at other locations, in sufficient numbers to be seen from any approach to this active portion. The legend shall be written in English and in any other language prevalent in the area surrounding the facility and must be legible from a distance of at least twenty five (25) feet. Existing signs with a legend other than "Danger -Unauthorized Personnel Keep Out" may be used if the legend on the sign indicates that only authorized personnel are allowed to enter the active portion, and that entry onto the active portion can be dangerous.
- 6. Termination of a Permit (40 C.F.R. 3 270.43)

The following are causes for terminating a permit during its term or for denying a permit renewal application:

- (a) Noncompliance with any condition of this permit; or
- (b) The permittee's failure in the application or during the permit issuance process to disclose fully all relevant facts, or the permittee's misrepresentation of any relevant facts at any time; or
- (c) A determination that the permitted activity endangers human health or the environment and can only be regulated to acceptable levels by permit modification or termination.
- 7. Operating Record (40 C.F.R. 3 264.73)

The permittee shall keep a written operating record at the facility in which the information required under 40 C.F.R. \rightarrow 264.73(b) shall be recorded. The information shall be recorded as it becomes available and maintained in the operating record until closure of the facility.

8. Permit Limitations (40 C.F.R. \rightarrow 270.4(c))

The issuance of this permit does not authorize any injury to persons or property or invasion of other private rights or any infringement of applicable Federal, State, or local laws or regulations.

- 9. Financial Requirements (40 C.F.R. Part 264 Subpart H)
 - (a) The permittee shall maintain financial responsibility for bodily injury and property damage to third parties caused by sudden accidental occurrences arising from operations of the facility. The permittee shall have and maintain liability coverage for sudden occurrences in the amount of at least \$1 million per occurrence with an annual aggregate of at least \$2 million exclusive of legal defense costs. The permittee shall demonstrate financial responsibility for sudden accidental occurrences according to the mechanisms given in 40 C.F.R. > 264.147 paragraphs (a)(1), (2), (3), (4), (5) or (6).
 - (b) The permittee shall establish financial assurance for closure of the facility. The permittee shall use a financial assurance mechanism approved by the Department, from the options specified in paragraphs (a) through (f) of 40 C.F.R. \rightarrow 264.143.
 - (C) The permittee shall have a detailed written closure cost estimate of closing the facility in accordance with 40 C.F.R. 3 264.142(a). The permittee shall adjust the closure cost estimate for inflation within sixty (60) days prior to the anniversary date of the establishment of the financial instrument(s) used to comply with 40 C.F.R. > 264.143. If the permittee uses the financial test or corporate guarantee, the closure cost estimate shall be updated for inflation within thirty (30) days after the close of the firm's fiscal year and before submission of the updated information to the Department. The adjustment may be made by recalculating the maximum costs of closure in current dollars, or by using an inflation factor derived from the most recent Implicit Price Deflator for Gross National Product published by the U.S. Department of Commerce in its Survey of Current Business. The inflation factor is the result of dividing the latest published annual Deflator by the Deflator for the previous year.

(1) The first adjustment is made by multiplying the

Page 16 of 42 Cycle Chem, Inc. HWF Permit

closure cost estimate by the inflation factor. The result is the adjusted closure cost estimate.

- (2) Subsequent adjustments are made by multiplying the latest adjusted closure cost estimate by the latest inflation factor.
- (d) During the active life of the facility, the permittee shall revise the closure cost estimate no later than (30) days after the Department has approved the request to modify the closure plan, if the change in the closure plan increases the cost of closure. The revised closure cost estimate must be adjusted for inflation as specified in 40 C.F.R.) 264.142(b).
- (e) The permittee shall keep at the facility during the operating life of the facility, the latest closure cost estimate prepared in accordance with 40 C.F.R. 264.142(a) and (c) and, when this estimate has been adjusted in accordance with 40 C.F.R. 264.142(b), the latest adjusted closure cost estimate.
- (f) The wording of all financial documents (except for the insurance policy itself) that are submitted under paragraphs (a), (b) and (c) of this Condition must be as per 40 C.F.R. 3 264.151 with the changes specified at N.J.A.C. 7:26G-8.1(c)8.
- 10. Compliance with Other State Regulations and Statutes

The permittee shall comply with all regulations of the Department of Environmental Protection and other State Statutes applicable to the facility. Regulations are effective upon publication in the New Jersey Register or as otherwise indicated in the Notice of Adoption in the New Jersey Register.

11. Submission of Documents Required by Permit Conditions

The permittee shall submit all permit compliance documents required by this permit to the following:

- (a) New Jersey Department of Environmental Protection Bureau of Hazardous Waste and Transfer Facilities P.O. Box 421 Trenton NJ 08625-0421
- (b) New Jersey Department of Environmental Protection Bureau of Hazardous Waste Compliance and Enforcement -P.O. Box 407 Robbinsville NJ 08625-0407
- 12. Referenced Permit Application Documents
 - (a) The permittee shall operate the facility, and construct or install associated appurtenances thereto, in

Page 17 of 42 Cycle Chem, Inc. HWF Permit

accordance with the regulations contained in 40 C.F.R. Parts 260 through 270, the conditions of this permit, and the following permit application documents:

- (1) The Part B Renewal Application dated May 27, 1994, submitted by Michael S. Persico, President, Cycle Chem, Inc.
- (2) The December 16, 1994, Response to the October 17, 1994, Technical Notice of Deficiency, submitted by Michael S. Persico, President, Cycle Chem, Inc.
- (3) Supplemental Information on the Lab Pack Processing Building dated February 17, 1995, submitted by Michael S. Persico, President, Cycle Chem, Inc.
- (4) Supplemental Information for the Part B Renewal Application dated September 29, 1995, submitted by Michael S. Persico, President, Cycle Chem, Inc.
- (5) Supplemental Information for the Part B Renewal Application dated May 14, 1996, June 21, 1996, July 2, 1996, and September 11, 1996, submitted by Jonathan C. Chewey, Regulatory Affairs Officer, Cycle Chem, Inc.
- (6) The following design drawings prepared by Leonard Engineering for Cycle Chem, Inc., signed and certified by John F. Shultis, P.E., New Jersey License No. 24289:

Drawing No.	Revision No.	Date
CCI-1496-1001A	1	04-15-92
CCI-1496-1002	4	04-15-92
CCI-1496-1003	2	04-15-92
CCI-1496-1004	1	04-15-92
CCI-1496-1005	1	04-15-92
CCI-1496-1006	3	05-05-94
CCI-1496-1007	3	05-05-94
CCI-1496-1008	1	04-15-92
CCI-1496-1009	1	04-15-92
CCI-1496-1010	3	06-24-92
CCI-1496-1011	5	05-05-94
CCI-1496-1012	5	05-05-94
CCI-1496-1013	3	05-05-94
CCI-1496-1014	3	05-05-94
CCI-1496-1015	0	05-05-94
		Modified 05/05/98
2575-1000	0	02-16-96

(7) Request for permit modification dated April 17, 1997, submitted by Jonathan C. Chewey, Regulatory Affairs Officer, Cycle Chem, Inc. Page 18 of 42 Cycle Chem, Inc. HWF Permit

(8) Assessment of Tank System Integrity dated April 30, 1997, submitted by Jonathan C. Chewey, Regulatory Affairs Officer, Cycle Chem, Inc.

Added 05/05/98

(9) Request for a Class 1 permit modification dated March 9, 1998, submitted by Jonathan C. Chewey, Regulatory Compliance Officer, Cycle Chem, Inc.

In case of conflict, the applicable hazardous waste management regulations contained in 40 C.F.R. shall have precedence over the conditions of this permit, and the conditions of this permit shall have precedence over the Part B permit application documents listed above.

- (b) One complete set of the permit application documents listed in Condition 12(a) above, this Hazardous Waste Facility Permit, and all records, reports and plans as may be required pursuant to this permit shall be kept onsite and shall be available for inspection by authorized representatives of the Department upon presentation of credentials. The records, reports and plans required pursuant to this permit include the following:
 - (1) The description of the personnel training program and the records required by Condition 2 of Section II of this permit and 40 C.F.R. **3** 264.16.
 - (2) The Contingency Plan required by Condition 4 of Section II of this permit and 40 C.F.R. 3 264.50, and specifically the plan submitted by Cycle Chem, Inc., dated June 21, 1996.
 - (3) The written Operating Record required by Condition 7 of Section II of this permit and 40 C.F.R. 3 264.73.
 - (4) Copies of the financial documents and closure cost estimate required by Condition 9 of Section II of this permit and 40 C.F.R. 264.140.
 - (5) The Waste Analysis Plan outlined in Condition 3 of Section III of this permit and as required by 40 C.F.R. 3 264.13, and specifically the plan submitted by Cycle Chem, Inc., dated May 27, 1994, with revisions dated December 16, 1994.

Modified 05/05/98

(6) The Inspection Schedule required by 40 C.F.R. 264.15(b) and the records required by Condition 4 of Section III of this permit.

Modified 05/05/98

(7) The Closure Plan required by Condition 5 of Section

Page 19 of 42 Cycle Chem, Inc. HWF Permit

III of this permit and 40 C.F.R. \rightarrow 264.112 and specifically the plan submitted by Cycle Chem, Inc., dated May 27, 1994, with revisions dated December 16, 1994 and March 1998.

End of Section II

Page 20 of 42 Cycle Chem, Inc. HWF Permit

Section III

Specific Facility Conditions Applicable to Cycle Chem Inc.

1. Authorized Activities

- (a) Storage in Containers
 - (1) The permittee is authorized to accept both commercially generated and onsite generated waste for storage, treatment, and transfer at the areas identified in the permit application documents and design drawings cited at Condition 12(a) of Section II of this permit, and as follows:

Area	Location	Container Type /Maximum Size	Area Capacity
Primary	Under All t	types up to 131,500	gallons
Storage	canopy	600 gallons	
Bulk	Under Tank	trucks up to 6,499)
Transfer	canopy	6,499 gallons	gallons
Secondary Storage	North side of site	Trucks, rolloffs, and containers up to 14,000 gallons	55,000 gallons
PCB Shed	East side of site	All types up to 500 500 gallons	gallons
Rejects	East side	All types up to 750	gallons
Shed	of site	600 gallons	
Lab Pack	NE corner	All types up to 3,355	5
Building	of site	600 gallons	gallons

- (2) The maximum amount of containerized waste in storage shall not exceed 152,499 gallons (equivalent to approximately 2,773 fifty-five gallon drums). Containers shall be stored only in the areas identified at Condition 1(a)1 of Section III of this permit.
- (3) Secondary containment systems shall be maintained for all areas identified at Condition 1(a)1 of Section III of this permit. The secondary containment systems shall be designed and operated in accordance with the permit application documents and design drawings cited at Condition 12(a) of Section II of this permit. Secondary containment systems shall be maintained free of cracks or gaps and be of adequate capacity and sufficient impermeability to contain leaks, spills, and accumulated rainfall until the collected material is detected and removed. Containment bases shall have

Page 21 of 42 Cycle Chem, Inc. HWF Permit

adequate structural integrity to withstand the maximum stress applied due to activities or structures placed in the containment areas. The secondary containment systems shall be maintained and operated to efficiently drain and remove liquids resulting from leaks, spills, and precipitation.

- (4) Spilled or leaked waste or accumulated precipitation shall be removed from the secondary containment systems in a timely manner, to prevent blockage or overflow of the collection system.
- (5) If a container holding hazardous waste is not in good condition (e.g., severe rusting, apparent structural defects) or if it begins to leak, the permittee shall transfer the hazardous waste from the container to a container that is in good condition or manage the waste in some other way that complies with the requirements of 40 C.F.R. 264.171.
- (6) The containers shall be managed in compliance with all provisions of 40 C.F.R. 3 264.173. Stacking height of containers or pallets of containers shall be limited to a maximum height the equivalent of three 55-gallon drums. Aisle space between rows of containers shall be maintained at a minimum of thirty (30) inches; except for containers or pallets of containers stacked the equivalent of one 55gallon drum in height upon which aisle space shall be maintained at a minimum of eighteen (18) inches.
- (7) The permittee shall not place a waste which is incompatible with waste already in a container, or incompatible with a material of construction of a container, in that container. The permittee shall not place a hazardous waste in an unwashed container which previously held an incompatible waste or material. The permittee shall evaluate each waste, prior to its addition to any container, to ensure compliance with 40 C.F.R. > 264.17(b).

(b) Storage/Treatment in Tanks

(1) The permittee is authorized to accept both commercially generated and onsite generated waste for storage, treatment, and transfer at the areas identified in the permit application documents and design drawings cited at Condition 12(a) of Section II of this permit, and as follows:

Tank	Volume	Primary
Number	(gallons)	Tank Use

Page 22 of 42 Cycle Chem, Inc. HWF Permit

1	7,500	Flammables
2	7,500	Flammables
3	7,500	Flammables
4	10,000	Flammables
5	7,500	Flammables
6	10,000	Flammables
7	7,500	Caustics
8	10,000	Caustics
9	7,500	Acids
10	7,500	Water/Solvent
11	7,500	Acids
12	7,500	Water/Solvent

- (2) The maximum tank storage capacity shall not exceed 97,500 gallons.
- (3) Secondary containment systems shall be maintained for all tanks identified at Condition 1(b)1 of Section III of this permit. The secondary containment systems shall be designed and operated in accordance with the permit application documents and design drawings cited at Condition 12(a) of Section II of this permit. Secondary containment systems shall be maintained free of cracks or gaps and shall have adequate capacity and impermeability to contain leaks, spills, and precipitation from a 25-year, 24-hour rainfall event until the collected material is detected and removed. The secondary containment systems shall be maintained and operated to efficiently drain and remove liquids resulting from leaks, spills, and precipitation.
- (4) Spilled or leaked waste and accumulated precipitation shall be removed from the secondary containment system within twenty four (24) hours, or in as timely a manner as is possible to prevent harm to human health and the environment.
- (5) The permittee shall operate the tanks in accordance with 40 C.F.R. 3 264.194.
- (6) The permittee shall comply with the requirements of 40 C.F.R. 3 264.198 for the management of ignitable or reactive wastes in the tanks authorized by Condition 1(b)1 of Section III of this permit.
- (7)The permittee shall comply with the requirements of 40 С.F.R. э 264.199 for the management of incompatible wastes in the tanks authorized by Condition 1(b)1 of Section III of this permit. The permittee shall not place a waste which is incompatible with the material of construction of a tank, in that tank, prior to compliance with 40 C.F.R. \mathbf{a} 264.17(b). The permittee shall not place a hazardous waste in a tank system that has not been decontaminated and that previously held an incompatible waste or material prior to compliance

Page 23 of 42 Cycle Chem, Inc. HWF Permit

with 40 C.F.R. > 264.17(b).

- (8) In response to leaks or spills and disposition of leaking or unfit for use tank systems, the permittee shall comply with the requirements cited at 40 C.F.R. 3 264.196 as follows:
 - (i) Cessation of use; prevent flow or addition of wastes. The owner or operator must immediately stop the flow of hazardous waste into the tank system or secondary containment system and inspect the system to determine the cause of the release.
 - (ii) Removal of waste from tank systems or secondary containment system.
 - (A) If the release was from a tank system, the permittee must, within 24 hours after detection of the leak or, if the permittee demonstrates that it is not possible, at the earliest practicable time, remove as much of the waste as is necessary to prevent further release of hazardous waste to the environment and to allow inspection and repair of the tank system to be performed.
 - (B) If the material released was to a secondary containment system, all released materials must be removed within 24 hours or in as timely a manner as is possible to prevent harm to human health and the environment.
 - (iii) Containment of visible releases to the environment. The permittee must immediately conduct a visual inspection of the release and, based upon that inspection:
 - (A) Prevent further migration of the leak or spill to soils or surface water; and
 - (B) Remove, and properly dispose of, any visible contamination of the soil or surface water.
 - (iv) Notifications, reports.
 - (A) Any release to the environment, except as provided in the following paragraph (iv)B, must be reported to the Department within 24 hours of its detection. If the release has been reported pursuant to 40 CFR part 302, that report will satisfy this requirement.

Page 24 of 42 Cycle Chem, Inc. HWF Permit

- (B) A leak or spill of hazardous waste is exempted from the requirements of this paragraph if it is:
 - (1) Less than or equal to a quantity of one (1) pound, and
 - (2) Immediately contained and cleaned up.
- (C) Within 30 days of detection of a release to the environment, a report containing the following information must be submitted to the Department:
 - Likely route of migration of the release;
 - (2) Characteristics of the surrounding soil (soil composition, geology, hydrogeology, climate);
 - (3) Results of any monitoring or sampling conducted in connection with the release (if available). If sampling or monitoring data relating to the release are not available within 30 days, these data must be submitted to the Department as soon as they become available.
 - (4) Proximity to downgradient drinking water, surface water, and populated areas; and
 - (5) Description of response actions taken or planned.
- (v) Provision of secondary containment, repair, or closure.
 - (A) Unless the permittee satisfies the requirements of the following paragraphs (v)(B) through (v)(D) of this section, the tank system must be closed in accordance with 40 C.F.R. \rightarrow 264.197 and Condition 5(a) of Section III of this permit.
 - (B) If the cause of the release was a spill that has not damaged the integrity of the system, the permittee may return the system to service as soon as the released waste is removed and repairs, if necessary, are made.
 - (C) If the cause of the release was a leak from the primary tank system into the secondary containment system, the system

must be repaired prior to returning the tank system to service.

- (D) If the source of the release was a leak to the environment from a component of a tank system without secondary containment, the permittee must provide the component of the system from which the leak occurred with secondary containment that satisfies the requirements of 40 C.F.R. 3 264.193 before it can be returned to service, unless the source of the leak is an aboveground portion of a tank system that can be inspected visually. If the source is an aboveground component that can be inspected visually, the component must be repaired and may be returned to service without secondary containment as long as the requirements of paragraph (vi) below of this section are satisfied. If a component is replaced to comply with the requirements of this subparagraph, that component must satisfy the requirements for new tank systems or components in 40 C.F.R. ЭЭ 264.192 and 264.193. Additionally, if a leak has occurred in any portion of a tank system component that is not readily accessible for visual inspection (e.g., the bottom of an inground or onground tank), the entire component must be provided with secondary containment in accordance with 40 C.F.R. 264.193 prior to being returned to use.
- (vi) Certification of major repairs. Ιf the permittee has repaired a tank system in accordance with paragraph (v) above, and the repair has been extensive (e.g., installation of an internal liner; repair of a ruptured primary containment or secondary containment vessel), the tank system must not be returned to service unless the permittee has obtained a certification by an independent, qualified, registered, professional engineer in accordance with 40 C.F.R. , 270.11(d) that the repaired system is capable of handling hazardous wastes without release for the intended life of the system. This certification must be submitted to the Department within seven days after returning the tank system to use.
- (c) Treatment Processes
 - (1) The permittee is authorized to conduct the following general types of physical and chemical treatment in containers, tanks, or within the concrete solidification chamber on bulk solids, semi-solids,

Page 26 of 42 Cycle Chem, Inc. HWF Permit

and sludges, utilizing ancillary equipment and materials as described in the permit application documents cited at Condition 12(a) of Section II of this permit:

grinding, shredding, crushing, and compacting; straining, filtering, and decanting; pouring, blending, mixing, and consolidating; bulking, thickening, stabilizing, and solidifying; fluidization, separation, emulsification, and pH adjustment.

- (2) The permittee is authorized to conduct the following specific treatment activities utilizing process methods, ancillary equipment, and materials as described in the permit application documents cited at Condition 12(a) of Section II of this permit:
 - (i) Treatment of wastewater by separation and carbon adsorption methods using a mobile wastewater separator and carbon adsorption unit to be stationed over the sump system on the south side of the tank farm under the canopy in the Primary Storage Area.
 - (ii) Treatment of sulfide bearing waste in containers by chlorination to be conducted in the Lab Pack Building or in a segregated location within the non-flammable storage area under the canopy in the Primary Storage Area. The amount of waste being treated at any one time shall not exceed fifty-five gallons (one drum).
 - (iii) Treatment of waste containing oxidizers in containers by hydration to be conducted in the Lab Pack Building or in a segregated location within the non-flammable storage area under the canopy in the Primary Storage Area. The amount of waste being treated at any one time shall not exceed fifty-five gallons (one drum).
 - (iv) Treatment of aerosols by carbon adsorption using a drum mounted system for the processing of aerosol cans to be stationed in a segregated location within the non-flammable storage area under the canopy in the Primary Storage Area.
 - (v) Treatment of solids, semi-solids, and sludges by consolidation, solidification, and stabilization methods to be conducted in the concrete solidification chamber located under the canopy. The total amount of material handled within the solidification chamber at any one time shall not exceed 70 cubic yards (approximately 14,000 gallons).

NOTE: The solidification chamber is authorized

Page 27 of 42 Cycle Chem, Inc. HWF Permit

for treatment purposes only and shall not be utilized for storage of waste under any circumstances.

- (vi) Treatment and processing, including packaging and re-packaging, of lab packed waste utilizing general treatment methods as identified in Condition 1(c)1, above, to be conducted in the Lab Pack Building or in a segregated location within the non-flammable storage area under the canopy in the Primary Storage Area. The total amount of lab packed waste being processed at any one time shall not exceed twenty (20) fifty-five gallon drums (1,100 gallons).
- (d) The permittee shall not store or treat hazardous waste at any location at the facility other than those authorized in (a), (b), and (c) above.
- (e) The permittee must obtain prior approval from the Department to make any changes or alterations to the authorized activities in this condition.

Page 28 of 42 Cycle Chem, Inc. HWF Permit

2. Authorized Wastes

(a) The permittee is authorized to accept shipments of the following wastes for storage, treatment, and transfer in containers or tanks:

Waste Number	Waste Identification or Description
All "D"	Solid waste which exhibits hazardous characteristics
F001-F012 F018-F019 F020-F028 F032 F034-F035 F037-F039	Hazardous waste from non-specific sources
K001-K011 K013-K052 K060-K062 K069 K071 K073 K083-K085 K086 K087 K093-K118 K123-K126 K131 K132 K136 K141-K145 K147-K151 K156-K161	Hazardous waste from specific sources
P001-P018 P020-P024 P026-P031	Commercial chemical products, manufacturing chemical intermediates, off-specification species, and spill residues thereof which are
P033	generally identified as acute hazardous waste
P034 P036-P051 P054 P056-P060 P062-P078 P081 P082 P084 P085 P087-P089 P092-P099 P101-P116 P118-P123	

P127-P128 P185 P188-P192 P194 P196-P199 P201-P205 U001-U012 Commercial chemical products, manufacturing U013-U053 chemical intermediates, off-specification U055-U064 species, and spill residues thereof which are U066-U099 generally identified as toxic hazardous waste U101-U103 U105-U174 U176-U194 U196-U223 U225-U228 U234-U237 U239 U240 U243 U244 U246-U249 U271 U277-U280 U328 U353 U359 U364-U367 U372-U373 U375-U379 U381-U396 U400-U404 U407 U409-U411 X910 Non-hazardous solid waste materials

ID72 Non-hazardous liquids and semi-liquids

3. Waste Analysis and Quality Assurance Requirements

The permittee shall adhere to the provisions of the waste analysis plan cited in Condition 12(b)5 of Section II of this permit and any subsequent revisions approved by the Department.

- (a) Each waste stream accepted at this location shall be fully identified and classified in accordance with 40 C.F.R. 3 264.13. At a minimum, the permittee shall develop all of the information which must be known to store and treat the waste onsite in accordance with the provisions of this permit, as well as to treat or dispose of the waste at authorized offsite facilities.
- The permittee must grant advanced authorization for (b) shipments of each waste stream from an off-site source. Prior to granting such authorization, the permittee shall obtain a completed material profile sheet and, if necessary to grant advanced authorization, а representative pre-shipment sample of the waste from the generator. The material profile sheet shall include, at a minimum, all of the information requested on the associated completion instructions included with the material profile sheet provided in the permit application documents cited at Condition 12(a) of Section II of this permit.

The quality control sample for each waste stream or the pre-shipment sample, when obtained, shall be analyzed in accordance with the test parameters and methods described in the table below utilizing the Quality Assurance/Quality Control methodologies established by the Department. the Department. The permittee shall review the analytical data to confirm that the permittee is authorized to accept the waste stream. The permittee must also confirm that (1)the data is sufficient for the intended ultimate destination facility, (2)the waste is acceptable to the intended ultimate stream destination facility, and (3) the generator does not disapprove of the ultimate destination facility or treatment/disposal method.

In addition, each waste stream handled at the facility shall be reviewed whenever (1)the generator informs the permittee of a change in the operation generating the waste, (2)a change in the character of the waste is observed during storage or treatment, or (3)annually, whichever is more frequent.

The following table details the analytical parameters and methods required for the development of analytical data for initial waste stream acceptance or waste stream review: Page 31 of 42 Cycle Chem, Inc. HWF Permit

Analytical Parameter Anal	lytical Method [*]
Color	Visual
Physical Characteristics	Visual
Flammability (Burn Test)	Visual
Compatibility**	Visual
Solubility	Visual
(water, solvent)	
Free Liquids	SW-846 9095
(paint filter test)	
Specific Gravity	ASTM D287-82, SMTD 2710F
Percent Solids	ASTM D4007-81
Radioactivity	Geiger Counter
Polychlorinated Biphenyls	SW 846 3620, 8080
Ignitability (flashpoint)	SW-846 1010,1020; ASTM D93-80
Corrosivity (pH)	SW-846 9040, 9041, 9045
Toxicity (TCLP)	SW-846 1311, 8260, 8270
Cyanide (spot)	SW-846 9010A, SMTD 4500
Sulfide (spot)	SW-846 9030, SMTD 4500
Ammonia (spot)	SMTD 4500
Oxidizer (spot)	STMD 4500
Total Organic Carbon	SW-846 9060, STMD 5310C
Percent Chlorine	SW-846 5050, 9252

Analytical methods are taken from ASTM, EPA Manual SW-846 3rd Edition, and/or Standard Methods for the Examination of Water & Wastewater 18th Edition (SMTD).

Compatibility testing shall be conducted on all waste streams to be bulked and/or blended at the facility in accordance with the waste analysis plan cited at Condition 12(b)5 of Section II of this permit. Compatibility testing shall be conducted in accordance with the following guidance documents: EPA Publication 600/2-80-076, Method for Determining the Compatibility of Hazardous Waste, and ASTM's publication, Estimating the Incompatibility of Selected Hazardous Wastes Based on Binary Chemical Reactions.

(C) Each shipment of waste from an off-site source shall be sampled and analyzed for "load verification" prior to acceptance by the permittee. For each bulk shipment of waste received, the permittee shall collect a representative sample compositing samples different bv several taken from locations/depths within the transport unit. For each containerized shipment of waste received, the permittee shall collect a representative sample from no less than ten (10) percent of containers holding the same waste stream from the same generator. These multiple samples from the same waste stream and generator may be composited for analysis.

Load verification testing shall be conducted on each incoming shipment of waste according to its anticipated method of treatment and/or ultimate disposal as identified in the permit application documents cited at Condition 12(a) of Section II of this permit and as follows: Page 32 of 42 Cycle Chem, Inc. HWF Permit

Parameter	Neutralize /Wastewater Treatment	Fuel Blend for Energy Recovery	Solvent Recovery	Incinerate /Thermal Treatment	e Land Disposal
Color	Х	Х	Х	Х	Х
Physical	Х	Х	Х	Х	Х
Characteristics	3				
Flammability				Х	Х
(Burn Test)					
Compatibility	Х	Х	Х	Х	Х
Specific Gravity	Į	Х	Х		
Miscibility		Х	Х	Х	Х
Solubility		Х	Х	Х	Х
(water, solvent	こ)				
Free Liquids					Х
(paint filter t	test)				
Percent Solids	Х				
Radioactivity	X	X	Х	X	X
Polychlorinated		X	Х	X	X
Biphenyls (non-	_				
aqueous waste)					
Ignitability			Х	Х	Х
(flashpoint)					
Corrosivity (pH) X	Х	Х	Х	X,
Toxicity (TCLP)					Х
Cyanide (spot)	Х				Х
Sulfide (spot)	X				X
Ammonia (spot)	Х				
Oxidizer (spot)	Х				Х
Total Organic Ca	arbon X				
Percent Chlorine	5	Х	Х	Х	

The results of load verification testing shall be compared to the data contained on the material profile sheet and/or developed from analysis of the initial acceptance sample to determine acceptability of the shipment.

^{*}Analysis required on hazardous waste streams only

- (d) The sampling and analytical requirements of Conditions 3(b) and (c), above, do not apply to individual containers or multiple container shipments to be accepted at the facility if adequate waste identification and handling information is available from a completed material profile sheet and/or material safety data sheet and if the shipment meets one of the following conditions:
 - (1) Container(s) accepted for storage and transfer only and will not be opened at the facility;
 - (2) Commercial products or materials packaged in their original un-opened container as provided by the manufacturer; or
 - (3) Inherently dangerous materials which would pose a significant threat to human health or the environment

Page 33 of 42 Cycle Chem, Inc. HWF Permit

(e.g., reactive waste, cyanides, sulfides, fuming
acids);

- (e) The permittee shall not accept any waste shipment which has not been adequately identified as specified in Conditions 3(a), (b), (c), and/or (d) of Section III of this permit. The permittee shall not accept any waste stream which is not authorized by Condition 2 of Section III of this permit.
- (f) The permittee shall adhere to the following regarding rejection of unauthorized waste shipments:
 - (1) The permittee shall not accept any waste unless the waste to be accepted is a waste for which the facility is authorized by Condition 2 of this section.
 - (2) The permittee, if offered hazardous waste of a type which the facility is not authorized to accept, shall:
 - (i) Not accept the waste from the hauler;
 - (ii) Instruct the hauler to contact the generator for further instructions;
 - (iii) Telephone the generator, and inform the generator that the permittee is not authorized to accept the waste and that the permittee has instructed the hauler to contact the generator for further instruction;

 - (v) Telephone the Department at (609)292-8341, and report the unauthorized waste shipment; and
 - (vi) Follow up the telephone call to the Department with a letter verifying the telephone conversation.
- (g) Sampling methods and all waste analyses performed shall be in accordance with the procedures outlined in the waste analysis plan cited in Condition 12(b)5 of Section II of this permit, and shall employ equipment and analysis methods as described in the latest edition of USEPA Manual SW-846 or as otherwise approved by the Department.
- (h) The permittee shall maintain in the written Operating Record required by Condition 7 of Section II of this Permit, as per 40 C.F.R. <u>3264.73(b)(3)</u>, records and results of all waste analyses performed. Such records and results shall be entered into the written Operating Record as they become available and shall be maintained until closure of the facility.
- (i) The permittee shall maintain the following information as per 40 C.F.R. $\frac{1}{2}$ 270.30(j)(3)in the written Operating Record:

Page 34 of 42 Cycle Chem, Inc. HWF Permit

- (1) The date, exact place, and time of sampling or measurements;
- (2) The individual(s) who performed the sampling or measurements;
- (3) The date(s) the analyses were performed;
- (4) The individual(s) who performed the analysis;
- (5) The analytical techniques or methods used; and
- (6) The results of the analysis.
- (j) No changes shall be made to the waste analysis plan without the prior approval of the Department.

4. Inspection Requirements (40 C.F.R. 3264.15, 3264.174, 3264.174 and 3 270.14(b)(5)

- (a) shall facility The permittee inspect the for malfunctions and deterioration, operator errors, and leaks or other discharges which may be a threat to human health and the environment. The permittee shall follow written inspection schedule for inspection of а operating areas, storage and treatment units, safety and general site safety emergency equipment, and and security devices as detailed in the permit application documents cited in Condition 12(a) of Section II of this permit and identified below. Results of the inspections shall be made part of the inspection log and shall be maintained as specified in Condition 4(c) of this section.
- (1) Container Storage Areas

Area/Item	Inspect For	Frequency
Containers	Number/Inventory	Weekly
	Damage Leaks	Weekly Weekly
	Labels Segregation by waste type	Weekly Weekly
	Aisle space Stacking height	Weekly Weekly
Pallets (when used)	Damage, deterioration	Weekly
Secondary Containment Systems	Cracks, spalling, uneven settlement, deterioration	Weekly

Page 35 of 42 Cycle Chem, Inc. HWF Permit

Spills, precipitation, Weekly debris

(2) Tank Storage Areas

Area/Item	Inspect For	Frequency
Tank Operation:		
Liquid level gauges	Function/Inventory	Daily
High level alarms	In-service Status Function	Daily Monthly
Waste feed cutoffs	In-service Status Function	Daily Monthly
Secondary Containment Systems	Cracks, spalling, uneven settlement, deterioration	Daily
	Spills, precipitation, debris	Daily
Tanks (internal):		
Roof	Corrosion, deterioration, cracking, perforations	Annual
Shell	Corrosion, deterioration, cracking, bulging, perforations	Annual
Bottom	Corrosion, deterioration, pits, depressions, seams, unevenness	Annual
Tanks (external):		
Tank identification number, markings	Visibility	Monthly
Shell, roof	Corrosion, deterioration, discoloration, bulging, cracking, perforations	Daily
Pipes, valves, fittings	Leaks, corrosion, damage, deterioration	Daily
Ladders, platforms, supports	Stability, damage, deterioration	Daily
Anchor bolts	Distortion, corrosion	Daily

(3) Safety/Emergency Equipment

Page 36 of 42 Cycle Chem, Inc. HWF Permit

Area/Item	Inspect For	Frequency
Alarms	Function	Weekly
Telephones, communication equipment	Function	Weekly
First aid supplies Protective clothing Safety showers	Availability Availability Function	Weekly Weekly Weekly
Spill control supplies	Availability	Weekly
Fire control systems and equipment	In-Service Status Function	Weekly Semi-annual
(4) General Facility Safety and Security		
Area/Item	Inspect For	Frequency
Housekeeping	Cleanliness, orderliness	Daily
Evacuation Routes	Obstructions	Daily
Fence, gates	Security, function	Daily
Warning signs	Availability, legibility	Daily

(b) Additional Inspections for Tank Systems

The permittee shall keep on file at the facility the written initial tank system assessment cited at Condition 12(a)8 of Section II of this permit, reviewed and certified by an independent, licensed professional engineer, in accordance with 40 C.F.R. \rightarrow 270.11(d), which attests to tank system integrity.

(2) Periodic Tank System Assessment

The permittee shall conduct periodic assessments of the storage tank and ancillary equipment in accordance with 40 C.F.R. \rightarrow 264.193(i) and as follows until such time as tank secondary containment meets the

Page 37 of 42 Cycle Chem, Inc. HWF Permit

requirements of 40 C.F.R. > 264.193.

- For the tank, the permittee shall either (i) conduct an annual leak test in accordance with 40 C.F.R. , 264.191(b)5 or develop a schedule and procedure for an assessment of the overall condition of the tank independent, licensed system by an professional engineer. The schedule and procedures must be adequate to detect obvious cracks, leaks, and corrosion or erosion that may lead to cracks and leaks. The owner or operator must remove the stored waste from the tank, if necessary, to allow the condition of all internal tank surfaces to be assessed. The frequency of these assessments must be based on the material of construction of the tank and its ancillary equipment, the age of the system, the type of corrosion or erosion protection used, the rate of corrosion or erosion observed during the previous inspection, and the characteristics of the waste being stored or treated.
- (ii) For ancillary equipment, a leak test or other integrity assessment approved by the Department, shall be conducted at least annually.
- (C) A log shall be kept of all inspections specified in Conditions 4(a) and (b), above, to confirm adequate maintenance of the hazardous waste storage and treatment units and all associated appurtenances. Results of all required inspections shall be maintained in the log at the facility for a minimum of three (3) years. At a minimum, this log must include the date and time of each inspection, the inspectors, a notation of the name of the observations made, and the date and nature of any repairs or other remedial actions performed.
- (d) The permittee shall remedy any deterioration or malfunction of equipment or structures which the inspection reveals on a schedule which ensures that the problem does not lead to an environmental or human health hazard. Where a hazard is imminent or has already occurred, remedial action shall be taken immediately.

If a tank system or component of a tank system is found to be leaking or unfit for use, the permittee must comply with the requirements of 40 C.F.R. \rightarrow 264.196 and Condition 1(b)8 of Section III of this permit. Equipment found to be leaking when Page 38 of 42 Cycle Chem, Inc. HWF Permit

inspected in accordance with 40 C.F.R. \rightarrow 264 Subpart BB, shall be repaired in accordance with the requirements of that Subpart. Records of inspections and repairs conducted in accordance with 40 C.F.R. \rightarrow 264 Subpart BB, shall be recorded in the inspection log identified in Condition 4(c) of Section III of this permit and shall include the information required by 40 C.F.R. \rightarrow 264.1064.

5. <u>Closure of Hazardous Waste Management Units (40 C.F.R.)</u> 264.110)

- (a) At the time of final closure, the permittee shall close the facility in the manner that is stated in 40 C.F.R. 3 264.110, in accordance with the closure plan referenced in Condition 12(b)7 of Section II of this permit, and the following:
 - (1) Within ninety (90) days from receipt of the final volume of waste, all waste in the container storage areas, tanks, treatment units, and associated equipment shall be shipped off-site to an authorized facility.
 - (2) Once empty, all tanks, piping, equipment, and associated structures shall be washed three (3) successive times with water, solvents, or other washing fluid which is compatible with waste which had been held within the tank system, and rinsed. High pressure washing or steam cleaning may be employed as necessary to remove waste residues. Once cleaned, tanks shall be entered for inspection and wiped or scraped as necessary to remove remaining residual material.

All container storage, tank storage, and treatment area secondary containment systems, including base, sidewalls, berms, and associated structures, shall be thoroughly washed, scrubbed, and rinsed. High pressure washing or steam cleaning may be employed as necessary to remove waste residues.

- (3) The wash and rinse wastes generated from the decontamination procedures described in Condition 5(a)2 above shall be collected for shipment offsite to an authorized facility.
- (4) Decontamination of tank units and all secondary containment systems at the facility shall be verified by collecting a sample of the final rinse liquid from each unit or area being decontaminated. These samples and a rinse blank shall be analyzed for hazardous waste characteristics, total volatile organics, total organic carbon, and polychlorinated biphenyls. Results of the analyses shall be submitted to the Department within one hundred

Page 39 of 42 Cycle Chem, Inc. HWF Permit

eighty (180) days from receipt of the final volume of waste. The Department will review the results and determine if the facility has been adequately decontaminated. Based on this determination, the permittee may be required to perform additional decontamination procedures.

- (5) All closure activities shall be completed within one hundred eighty (180) days from receipt of the final volume of waste.
- The permittee shall submit certification by both (6) the owner or operator and an independent professional engineer, licensed in the State of New Jersey, that the facility has been closed in accordance with the closure plan specifications. certification shall be submitted to the The Department within two hundred forty (240) days from the date of implementation of the closure plan, in accordance with 40 C.F.R. 3264.115.
- (7) The Department will review the certification will conduct a documentation and closure certification inspection. If the closure certification documents are complete and there is a satisfactory closure certification inspection, the closure certification will be accepted by the Department and the closure will be deemed complete.
- (b) The permittee shall keep a copy of the closure plan and all revisions to the plan at the facility until closure is completed.
- (c) The permittee shall amend the closure plan any time changes in operating plans or facility design affect the closure plan or whenever there is a change in the expected year of closure of the facility. The permittee must comply with the requirement cited at 40 C.F.R. $_{264.112(c)(3)}$ for amendment of closure plan.
- (d) The permittee shall notify the Department at least forty five (45) days prior to the date the permittee expects to begin closure, except in cases where the facility's permit is terminated or if the facility is otherwise ordered by judicial decrees or compliance order to close. The date when the owner or operator "expects to begin closure" shall be within thirty (30) days after the date on which the owner or operator expects to receive the final volume of wastes.
- 6. <u>Construction/Installation Requirements</u>
 - The permittee will be authorized to upgrade (a) the secondary containment units for all storage and treatment tanks and ancillary equipment associated with tank systems. The permittee shall submit, at least sixty days prior to initiation of (60) the upgrade construction, final plans, specifications, and

Page 40 of 42 Cycle Chem, Inc. HWF Permit

engineering design drawings, as applicable, to the Department at the address listed in Condition 11(a) of Section II of this permit, for review and approval. The permittee shall also apply for and obtain all applicable local authority approvals and building permits prior to initiation of construction.

- (b) The permittee shall complete the upgrades to the secondary containment in conformance with 40 C.F.R. 264.193(a)3.
- (c) The permittee shall submit to the Department, at the address listed in Condition 11(a) of Section II of this permit, reports of progress toward completion of work at three (3) month intervals, until construction is completed. The first report shall be due thirty (30) days prior to commencement of construction.
- (d) The Department will inspect the completed upgrades to the storage and treatment tank secondary containment systems for substantial conformance with the approved plans, specifications, and/or engineering design drawings referenced in Condition 6(a) above. If the facility is found not in substantial conformance with the approved design, a schedule shall be submitted within thirty (30) days of the date of the Department's inspection outlining how the facility will be brought into conformance. The schedule shall be submitted to the Department for approval.

7. Additional Part B Permit Application Requirements

The permittee shall submit the following additional Part B permit application information within 180 days of the date of permit reissuance in order to update the application to conform to 40 C.F.R. Parts 260 through 270.

- (a) A detailed description of any ancillary equipment which meets the exemption from secondary containment requirements of 40 C.F.R. > 264.193(f).
- (b) A revised Inspection Plan which includes a schedule and procedures for conducting leak tests or other integrity assessments of the tank system required by Condition 4(b)2 of Section III of this permit. Daily visual inspections of any ancillary equipment which meets the exemption outlined in Condition 7(a) above shall also be incorporated into the plan.
- (c) A detailed description of procedures to be carried out in response to leaks or spills and when shutting down or repairing a leaking tank as required in Condition 1(b)8 of Section III of this permit.
- (d) A revised Closure Plan which includes a contingent closure and post-closure care plan, revised closure cost

Page 41 of 42 Cycle Chem, Inc. HWF Permit

estimates, and a demonstration of financial assurance to meet the contingent post-closure care provisions of 40 C.F.R. \rightarrow 264.197(c).

End of Section III

DOCUMENT: CYCHEM07.PER