



Right to Know Hazardous Substance Fact Sheet

Common Name: **BUTYL ACRYLATE**

Synonyms: Acrylic Acid Butyl Ester

Chemical Name: 2-Propenoic Acid, Butyl Ester

Date: November 2007 Revision: April 2017

CAS Number: 141-32-2

RTK Substance Number: 0278

DOT Number: UN 2348

Description and Use

Butyl Acrylate is a clear, colorless liquid with a fruity, strong odor. It is used in the manufacture of polymers and resins, and in paint formulations.

- ▶ **ODOR THRESHOLD=0.035 ppm**
- ▶ Odor thresholds vary greatly. Do not rely on odor alone to determine potentially hazardous exposures.

Reasons for Citation

- ▶ **Butyl Acrylate** is on the Right to Know Hazardous Substance List because it is cited by ACGIH, DOT, NIOSH, DEP, IARC, NFPA and EPA.
- ▶ This chemical is on the Special Health Hazard Substance List.

[SEE GLOSSARY ON PAGE 5.](#)

FIRST AID

Eye Contact

- ▶ Immediately flush with large amounts of water for at least 15 minutes, lifting upper and lower lids. Remove contact lenses, if worn, while flushing. Seek medical attention.

Skin Contact

- ▶ Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of soap and water.

Inhalation

- ▶ Remove the person from exposure.
- ▶ Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- ▶ Transfer promptly to a medical facility.

EMERGENCY NUMBERS

Poison Control: 1-800-222-1222

CHEMTREC: 1-800-424-9300

NJDEP Hotline: 1-877-927-6337

National Response Center: 1-800-424-8802

EMERGENCY RESPONDERS >>>> SEE BACK PAGE

Hazard Summary

Hazard Rating	NJDOH	NFPA
HEALTH	3	2
FLAMMABILITY	3	2
REACTIVITY	2	2
FLAMMABLE REACTIVE POISONOUS GASES ARE PRODUCED IN FIRE CONTAINERS MAY EXPLODE IN FIRE		

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious; 4=severe

- ▶ **Butyl Acrylate** can affect you when inhaled and by passing through the skin.
- ▶ Contact can irritate and burn the skin and eyes.
- ▶ Inhaling **Butyl Acrylate** can irritate the nose, throat and lungs.
- ▶ **Butyl Acrylate** may cause a skin allergy.
- ▶ Exposure to **Butyl Acrylate** can cause headache, dizziness, nausea and vomiting.
- ▶ Repeated exposure can lead to permanent lung damage.
- ▶ **Butyl Acrylate** is FLAMMABLE and REACTIVE and a DANGEROUS FIRE and EXPLOSION HAZARD.

Workplace Exposure Limits

NIOSH: The recommended airborne exposure limit (REL) is **10 ppm** averaged over a 10-hour workshift.

ACGIH: The threshold limit value (TLV) is **2 ppm** averaged over an 8-hour workshift.

- ▶ The above exposure limits are for air levels only. When skin contact also occurs, you may be overexposed, even though air levels are less than the limit's listed above.

Determining Your Exposure

- ▶ Read the product manufacturer's Material Safety Data Sheet (MSDS) and the label to determine product ingredients and important safety and health information about the product mixture.
- ▶ For each individual hazardous ingredient, read the New Jersey Department of Health and Senior Services Hazardous Substance Fact Sheet, available on the RTK Program website (<http://nj.gov/health/workplacehealthandsafety/right-to-know/>) or in your facility's RTK Central File or Hazard Communication Standard file.
- ▶ You have a right to this information under the New Jersey Worker and Community Right to Know Act, the Public Employees Occupational Safety and Health (PEOSH) Act if you are a public worker in New Jersey, and under the federal Occupational Safety and Health Act (OSHA) if you are a private worker.
- ▶ The New Jersey Right to Know Act and the PEOSH Hazard Communication Standard (N.J.A.C. 12:100-7) requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard (29 CFR 1910.1200) requires private employers to provide similar information and training to their employees.

This Fact Sheet is a summary of available information regarding the health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

Health Hazard Information

Acute Health Effects

The following acute (short-term) health effects may occur immediately or shortly after exposure to **Butyl Acrylate**:

- ▶ Contact can irritate and burn the skin and eyes.
- ▶ Inhaling **Butyl Acrylate** can irritate the nose, throat and lungs causing coughing, wheezing and/or shortness of breath.
- ▶ Exposure to **Butyl Acrylate** can cause headache, dizziness, nausea and vomiting.

Chronic Health Effects

The following chronic (long-term) health effects can occur at some time after exposure to **Butyl Acrylate** and can last for months or years:

Cancer Hazard

- ▶ While **Butyl Acrylate** has been tested, it is not classifiable as to its potential to cause cancer.

Reproductive Hazard

- ▶ According to the information presently available to the New Jersey Department of Health, **Butyl Acrylate** has been tested and has not been shown to affect reproduction.

Other Effects

- ▶ **Butyl Acrylate** may cause a skin allergy. If allergy develops, very low future exposure can cause itching and a skin rash.
- ▶ Repeated exposure can lead to permanent lung damage.

Medical

Medical Testing

If symptoms develop or overexposure is suspected, the following are recommended:

- ▶ Chest x-ray and lung function tests
- ▶ Evaluation by a qualified allergist can help diagnose skin allergy.

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are not a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under the OSHA Access to Employee Exposure and Medical Records Standard (29 CFR 1910.1020).

Mixed Exposures

- ▶ Smoking can cause heart disease, lung cancer, emphysema, and other respiratory problems. It may worsen respiratory conditions caused by chemical exposure. Even if you have smoked for a long time, stopping now will reduce your risk of developing health problems.

Workplace Controls and Practices

Very toxic chemicals, or those that are reproductive hazards or sensitizers, require expert advice on control measures if a less toxic chemical cannot be substituted. Control measures include: (1) enclosing chemical processes for severely irritating and corrosive chemicals, (2) using local exhaust ventilation for chemicals that may be harmful with a single exposure, and (3) using general ventilation to control exposures to skin and eye irritants. For further information on workplace controls, consult the NIOSH document on Control Banding at www.cdc.gov/niosh/topics/ctrlbanding/.

The following work practices are also recommended:

- ▶ Label process containers.
- ▶ Provide employees with hazard information and training.
- ▶ Monitor airborne chemical concentrations.
- ▶ Use engineering controls if concentrations exceed recommended exposure levels.
- ▶ Provide eye wash fountains and emergency showers.
- ▶ Wash or shower if skin comes in contact with a hazardous material.
- ▶ Always wash at the end of the workshift.
- ▶ Change into clean clothing if clothing becomes contaminated.

- ▶ Do not take contaminated clothing home.
- ▶ Get special training to wash contaminated clothing.
- ▶ Do not eat, smoke, or drink in areas where chemicals are being handled, processed or stored.
- ▶ Wash hands carefully before eating, smoking, drinking, applying cosmetics or using the toilet.

In addition, the following may be useful or required:

- ▶ Before entering a confined space where **Butyl Acrylate** may be present, check to make sure that an explosive concentration does not exist.

Personal Protective Equipment

The OSHA Personal Protective Equipment Standard (29 CFR 1910.132) requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

Gloves and Clothing

- ▶ Avoid skin contact with **Butyl Acrylate**. Wear personal protective equipment made from material which can not be permeated or degraded by this substance. Safety equipment suppliers and manufacturers can provide recommendations on the most protective glove and clothing material for your operation.
- ▶ Safety equipment manufacturers recommend *4-H®/Silver Shield®* for gloves and *DuPont Tychem® Responder* and *TK* as protective materials for clothing.
- ▶ All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.

Eye Protection

- ▶ Wear indirect-vent, impact and splash resistant goggles when working with liquids.
- ▶ Wear a face shield along with goggles when working with corrosive, highly irritating or toxic substances.
- ▶ Do not wear contact lenses when working with this substance.

Respiratory Protection

Improper use of respirators is dangerous. Respirators should only be used if the employer has a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing, and medical exams, as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134).

- ▶ Where the potential exists for exposure over **2 ppm**, use a NIOSH approved full facepiece respirator with an organic vapor cartridge. Increased protection is obtained from full facepiece powered-air purifying respirators.
- ▶ Leave the area immediately if (1) while wearing a filter or cartridge respirator you can smell, taste, or otherwise detect **Butyl Acrylate**, (2) while wearing particulate filters abnormal resistance to breathing is experienced, or (3) eye irritation occurs while wearing a full facepiece respirator. Check to make sure the respirator-to-face seal is still good. If it is, replace the filter or cartridge. If the seal is no longer good, you may need a new respirator.

- ▶ Consider all potential sources of exposure in your workplace. You may need a combination of filters, prefilters or cartridges to protect against different forms of a chemical (such as vapor and mist) or against a mixture of chemicals.
- ▶ Where the potential exists for exposure over **100 ppm**, use a NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus operated in a pressure-demand or other positive-pressure mode.

Fire Hazards

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA Fire Brigades Standard (29 CFR 1910.156).

- ▶ **Butyl Acrylate** is a FLAMMABLE LIQUID.
- ▶ Use dry chemical, CO₂, water spray or foam as extinguishing agents.
- ▶ POISONOUS GASES ARE PRODUCED IN FIRE.
- ▶ CONTAINERS MAY EXPLODE IN FIRE.
- ▶ Use water spray to keep fire-exposed containers cool.
- ▶ Vapors may travel to a source of ignition and flash back.
- ▶ Vapor is heavier than air and may travel a distance to cause a fire or explosion far from the source.

Spills and Emergencies

If employees are required to clean-up spills, they must be properly trained and equipped. The OSHA Hazardous Waste Operations and Emergency Response Standard (29 CFR 1910.120) may apply.

If **Butyl Acrylate** is spilled or leaked, take the following steps:

- ▶ Evacuate personnel and secure and control entrance to the area.
- ▶ Eliminate all ignition sources.
- ▶ Absorb liquids in vermiculite, dry sand, earth, or a similar material and deposit in sealed containers.
- ▶ Ventilate and wash area after clean-up is complete.
- ▶ Keep **Butyl Acrylate** out of confined spaces, such as sewers, because of the possibility of an explosion.
- ▶ It may be necessary to contain and dispose of **Butyl Acrylate** as a HAZARDOUS WASTE. Contact your state Department of Environmental Protection (DEP) or your regional office of the federal Environmental Protection Agency (EPA) for specific recommendations.

Handling and Storage

Prior to working with **Butyl Acrylate** you should be trained on its proper handling and storage.

- ▶ **Butyl Acrylate** is REACTIVE and can easily polymerize with HEAT, LIGHT, or by catalytic reaction with METALS.
- ▶ **Butyl Acrylate** reacts violently with OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE) to cause fires and explosions.
- ▶ **Butyl Acrylate** is not compatible with STRONG ACIDS (such as HYDROCHLORIC, SULFURIC and NITRIC); STRONG BASES (such as SODIUM HYDROXIDE and POTASSIUM HYDROXIDE); AMINES; and HYDROGEN COMPOUNDS.
- ▶ Store in tightly closed containers in a cool, well-ventilated area away from HEAT, FLAME, and SUNLIGHT.
- ▶ Sources of ignition, such as smoking and open flames, are prohibited where **Butyl Acrylate** is used, handled, or stored.
- ▶ Use explosion-proof electrical equipment and fittings wherever **Butyl Acrylate** is used, handled, manufactured, or stored.
- ▶ **Butyl Acrylate** undergoes auto polymerization (self-react) and should be stored with an inhibitor.
- ▶ Protect against physical damage. Outside or detached storage is preferred. Inside storage should be in a standard storage room for flammables.

Occupational Health Information Resources

The New Jersey Department of Health offers multiple services in occupational health. These services include providing informational resources, educational materials, public presentations, and industrial hygiene and medical investigations and evaluations.

For more information, please contact:

New Jersey Department of Health
Right to Know Program
PO Box 368
Trenton, NJ 08625-0368
Phone: 609-984-2202
Fax: 609-984-7407
E-mail: rtk@doh.nj.gov
Web address:
<http://nj.gov/health/workplacehealthandsafety/right-to-know/>

***The Right to Know Hazardous Substance Fact Sheets
are not intended to be copied and sold
for commercial purposes.***

GLOSSARY

ACGIH is the American Conference of Governmental Industrial Hygienists. They publish guidelines called Threshold Limit Values (TLVs) for exposure to workplace chemicals.

Acute Exposure Guideline Levels (AEGs) are established by the EPA. They describe the risk to humans resulting from once-in-a-lifetime, or rare, exposure to airborne chemicals.

Boiling point is the temperature at which a substance can change its physical state from a liquid to a gas.

A **carcinogen** is a substance that causes cancer.

The **CAS number** is unique, identifying number, assigned by the Chemical Abstracts Service, to a specific chemical.

CFR is the Code of Federal Regulations, which are the regulations of the United States government.

A **combustible** substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes destruction of human skin or severe corrosion of containers.

DEP is the New Jersey Department of Environmental Protection.

DOT is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

EPA is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

ERG is the Emergency Response Guidebook. It is a guide for emergency responders for transportation emergencies involving hazardous substances.

Emergency Response Planning Guideline (ERPG) values are intended to provide estimates of concentration ranges where one reasonably might anticipate observing adverse effects.

A **fetus** is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

IARC is the International Agency for Research on Cancer, a scientific group.

Ionization Potential is the amount of energy needed to remove an electron from an atom or molecule. It is measured in electron volts.

IRIS is the Integrated Risk Information System database maintained by federal EPA. The database contains information on human health effects that may result from exposure to various chemicals in the environment.

LEL or Lower Explosive Limit, is the lowest concentration of a combustible substance (gas or vapor) in the air capable of continuing an explosion.

mg/m³ means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

NFPA is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

NIOSH is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

NTP is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

OSHA is the federal Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

PEOSHA is the New Jersey Public Employees Occupational Safety and Health Act, which adopts and enforces health and safety standards in public workplaces.

Permeated is the movement of chemicals through protective materials.

PIH is a DOT designation for chemicals which are Poison Inhalation Hazards.

ppm means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

STEL is a Short Term Exposure Limit which is usually a 15-minute exposure that should not be exceeded at any time during a work day.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

UEL or Upper Explosive Limit is the highest concentration in air above which there is too much fuel (gas or vapor) to begin a reaction or explosion.

Vapor Density is the ratio of the weight of a given volume of one gas to the weight of another (usually *Hydrogen*), at the same temperature and pressure.

The **vapor pressure** is a measure of how readily a liquid or a solid mixes with air at its surface. A higher vapor pressure indicates a higher concentration of the substance in air and therefore increases the likelihood of breathing it in.

Common Name: **BUTYL ACRYLATE**

Synonyms: Acrylic Acid Butyl Ester

CAS No: 141-32-2

Molecular Formula: C₇H₁₂O₂

RTK Substance No: 0278

Description: Clear, colorless liquid with a fruity, strong odor

HAZARD DATA

Hazard Rating	Firefighting	Reactivity
<p>3 - Health</p> <p>3 - Fire</p> <p>2 - Reactivity</p> <p>DOT#: UN 2348</p> <p>ERG Guide #: 130P</p> <p>Hazard Class: 3 (Flammable)</p>	<p>Use dry chemical, CO₂, water spray or foam as extinguishing agents.</p> <p>POISONOUS GASES ARE PRODUCED IN FIRE.</p> <p>CONTAINERS MAY EXPLODE IN FIRE.</p> <p>Use water spray to keep fire-exposed containers cool.</p> <p>Vapors may travel to a source of ignition and flash back.</p> <p>Vapor is heavier than air and may travel a distance to cause a fire or explosion far from the source.</p>	<p>Butyl Acrylate is REACTIVE and can easily polymerize with HEAT, LIGHT, or by catalytic reaction with METALS.</p> <p>Butyl Acrylate reacts violently with OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE) to cause fires and explosions.</p> <p>Butyl Acrylate is not compatible with STRONG ACIDS (such as HYDROCHLORIC, SULFURIC and NITRIC); STRONG BASES (such as SODIUM HYDROXIDE and POTASSIUM HYDROXIDE); AMINES; and HYDROGEN COMPOUNDS.</p>

SPILL/LEAKS
<p>Isolation Distance:</p> <p>Small Spill - 60 meters (200 feet)</p> <p>Large Spill - 270 meters (900 feet)</p> <p>Absorb liquids in vermiculite, dry sand, earth, or a similar material and deposit in sealed containers.</p> <p>Toxic to aquatic organisms.</p>

PHYSICAL PROPERTIES
<p>Odor Threshold: 0.035 ppm</p> <p>Flash Point: 97.7°F (36.5°C)</p> <p>LEL: 1.1%</p> <p>UEL: 9.9%</p> <p>Relative Density: 0.9 (water = 1)</p> <p>Vapor Density: 4.42 (air = 1)</p> <p>Vapor Pressure: 4 mm Hg at 68°F (20°C)</p> <p>Water Solubility: Slightly soluble</p> <p>Boiling Point: 293° to 300°F (145° to 149°C)</p> <p>Molecular Weight: 128.2</p>

EXPOSURE LIMITS
<p>OSHA: None</p> <p>NIOSH: 10 ppm, 10-hr TWA</p> <p>ACGIH: 2 ppm, 8-hr TWA</p> <p>IDLH LEVEL: No information</p> <p>PAC LEVELS: PAC-1 = 8.3 ppm; PAC-2 = 130 ppm; PAC-3 = 480 ppm</p>

PROTECTIVE EQUIPMENT
<p>Gloves: 4-H®/Silver Shield® (>8-hr breakthrough)</p> <p>Coveralls: DuPont Tychem® Responder and TK (>8-hr breakthrough)</p> <p>Boots: No information</p> <p>Respirator: >2 ppm - full facepiece APR with Organic Vapor cartridges >100 ppm – Pressure demand supplied-air</p>

HEALTH EFFECTS
<p>Eyes: Irritation and burns</p> <p>Skin: Irritation and burns</p> <p>Acute: Irritation of nose, throat and lungs with coughing, wheezing, and/or shortness of breath</p> <p>Chronic: Headache, dizziness and vomiting Skin allergy with itching, redness and rash</p>

FIRST AID AND DECONTAMINATION
<p>Remove the person from exposure.</p> <p>Flush eyes with large amounts of water for at least 15 minutes. Remove contact lenses if worn. Seek medical attention.</p> <p>Quickly remove contaminated clothing and wash contaminated skin with large amounts of soap and water. Seek medical attention.</p> <p>Begin artificial respiration if breathing has stopped and CPR if necessary.</p> <p>Transfer to a medical facility.</p>