



# Right to Know Hazardous Substance Fact Sheet

Common Name: **CACODYLIC ACID**

Synonyms: Hydroxydimethylarsine Oxide

Chemical Name: Arsinic Acid, Dimethyl-

Date: January 1999      Revision: July 2008

CAS Number: 75-60-5

RTK Substance Number: 0304

DOT Number: UN 1572

## Description and Use

**Cacodylic Acid** is an *organic Arsenic compound*. It is a colorless to white, odorless, crystalline (sand-like) solid that is used as a herbicide and soil sterilant. It is also used in chemical warfare and in timber thinning.

## Reasons for Citation

- ▶ **Cacodylic Acid** is on the Right to Know Hazardous Substance List because it is cited by OSHA, DOT, DEP, IARC, IRIS and EPA.
- ▶ This chemical is on the Special Health Hazard Substance List.

SEE GLOSSARY ON PAGE 5.

## FIRST AID

### Eye Contact

- ▶ Immediately flush with large amounts of water for at least 15 minutes, lifting upper and lower lids. Remove contact lenses, if worn, while flushing. Seek medical attention.

### Skin Contact

- ▶ Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of water.

### Inhalation

- ▶ Remove the person from exposure.
- ▶ Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- ▶ Transfer promptly to a medical facility.

## EMERGENCY NUMBERS

Poison Control: 1-800-222-1222

CHEMTREC: 1-800-424-9300

NJDEP Hotline: 1-877-927-6337

National Response Center: 1-800-424-8802

EMERGENCY RESPONDERS >>>> SEE BACK PAGE

## Hazard Summary

Hazard Rating	NJDOH	NFPA
HEALTH	4	-
FLAMMABILITY	0	-
REACTIVITY	0	-
CARCINOGEN POISONOUS GASES ARE PRODUCED IN FIRE DOES NOT BURN		

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious; 4=severe

- ▶ **Cacodylic Acid** can affect you when inhaled and by passing through the skin.
- ▶ **Cacodylic Acid** is a CARCINOGEN. HANDLE WITH EXTREME CAUTION.
- ▶ Skin contact can cause irritation, burns, rash and loss of pigment.
- ▶ Eye contact can cause irritation and burns.
- ▶ Inhaling **Cacodylic Acid** can irritate the nose and throat and can cause an ulcer or hole in the "bone" (septum) dividing the inner nose.
- ▶ Exposure to **Cacodylic Acid** can cause weakness, poor appetite, headache and even death.
- ▶ **Cacodylic Acid** may damage the nervous system and the liver

## Workplace Exposure Limits

The following exposure limit is for *organic Arsenic compounds* (measured as *Arsenic*):

OSHA: The legal airborne permissible exposure limit (PEL) is **0.5 mg/m<sup>3</sup>** averaged over an 8-hour workshift.

- ▶ **Cacodylic Acid** is a CARCINOGEN in humans. There may be no safe level of exposure to a carcinogen, so all contact should be reduced to the lowest possible level.
- ▶ The above exposure limit is for air levels only. When skin contact also occurs, you may be overexposed, even though air levels are less than the limit listed above.

## Determining Your Exposure

- ▶ Read the product manufacturer's Material Safety Data Sheet (MSDS) and the label to determine product ingredients and important safety and health information about the product mixture.
- ▶ For each individual hazardous ingredient, read the New Jersey Department of Health Hazardous Substance Fact Sheet, available on the RTK website ([www.nj.gov/health/eoh/rtkweb](http://www.nj.gov/health/eoh/rtkweb)) or in your facility's RTK Central File or Hazard Communication Standard file.
- ▶ You have a right to this information under the New Jersey Worker and Community Right to Know Act, the Public Employees Occupational Safety and Health (PEOSH) Act if you are a public worker in New Jersey, and under the federal Occupational Safety and Health Act (OSHA) if you are a private worker.
- ▶ The New Jersey Right to Know Act requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard (29 CFR 1910.1200) and the PEOSH Hazard Communication Standard (N.J.A.C. 12:100-7) require employers to provide similar information and training to their employees.

This Fact Sheet is a summary of available information regarding the health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

## Health Hazard Information

### Acute Health Effects

The following acute (short-term) health effects may occur immediately or shortly after exposure to **Cacodylic Acid**:

- ▶ Skin contact can cause irritation, burns, itching, rash and loss of pigment.
- ▶ Eye contact can cause irritation, burns, and red, watery eyes.
- ▶ Inhaling **Cacodylic Acid** can irritate the nose and throat causing coughing and wheezing.
- ▶ Exposure to **Cacodylic Acid** can cause weakness, poor appetite, nausea, vomiting, headache, muscle cramps, and even death.

### Chronic Health Effects

The following chronic (long-term) health effects can occur at some time after exposure to **Cacodylic Acid** and can last for months or years:

### Cancer Hazard

- ▶ **Cacodylic Acid** is a CARCINOGEN in humans. There is evidence that *Arsenic* and *Arsenic compounds* cause bladder, lung, and skin cancer in humans.
- ▶ Many scientists believe there is no safe level of exposure to a carcinogen.

### Reproductive Hazard

- ▶ There is limited evidence that **Cacodylic Acid** is a teratogen in animals. Until further testing has been done, it should be treated as a possible teratogen in humans.

### Other Effects

- ▶ Repeated skin contact can cause thickened skin and/or patchy areas of darkening and loss of pigment. Some persons may develop white lines on the nails.
- ▶ Long-term exposure can cause an ulcer or hole in the "bone" (septum) dividing the inner nose, hoarseness and sore eyes.
- ▶ **Cacodylic Acid** may damage the nervous system causing numbness, "pins and needles," and/or weakness in the hands and feet.
- ▶ **Cacodylic Acid** may damage the liver.

## Medical

### Medical Testing

Before beginning employment and at regular times thereafter, (at least annually), the following are recommended:

- ▶ Chest x-ray
- ▶ Exam of the nose, skin and nails
- ▶ Test for urine *Arsenic*. This is most accurate at the end of the workday. Eating shellfish or fish may elevate *Arsenic* levels for up to two days. At NIOSH recommended exposure levels, urine *Arsenic* should not be greater than **100 micrograms per liter** of urine.

After suspected overexposure, repeat these tests and consider an exam of the nervous system and liver function tests. Also examine your skin periodically for abnormal growths. Skin cancer from *Arsenic* can be easily cured when detected early.

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are not a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under the OSHA Access to Employee Exposure and Medical Records Standard (29 CFR 1910.1020).

### Mixed Exposures

- ▶ More than light alcohol consumption can cause liver damage. Drinking alcohol may increase the liver damage caused by **Cacodylic Acid**.

### Conditions Made Worse By Exposure

- ▶ Many scientists believe that skin changes, such as thickening and pigment changes, make those skin areas more likely to develop skin cancer.

## Workplace Controls and Practices

Very toxic chemicals, or those that are reproductive hazards or sensitizers, require expert advice on control measures if a less toxic chemical cannot be substituted. Control measures include: (1) enclosing chemical processes for severely irritating and corrosive chemicals, (2) using local exhaust ventilation for chemicals that may be harmful with a single exposure, and (3) using general ventilation to control exposures to skin and eye irritants. For further information on workplace controls, consult the NIOSH document on Control Banding at [www.cdc.gov/niosh/topics/ctrlbanding/](http://www.cdc.gov/niosh/topics/ctrlbanding/).

The following work practices are also recommended:

- ▶ Label process containers.
- ▶ Provide employees with hazard information and training.
- ▶ Monitor airborne chemical concentrations.
- ▶ Use engineering controls if concentrations exceed recommended exposure levels.
- ▶ Provide eye wash fountains and emergency showers.
- ▶ Wash or shower if skin comes in contact with a hazardous material.
- ▶ Always wash at the end of the workshift.
- ▶ Change into clean clothing if clothing becomes contaminated.
- ▶ Do not take contaminated clothing home.
- ▶ Get special training to wash contaminated clothing.
- ▶ Do not eat, smoke, or drink in areas where chemicals are being handled, processed or stored.
- ▶ Wash hands carefully before eating, smoking, drinking, applying cosmetics or using the toilet.

In addition, the following may be useful or required:

- ▶ Use a vacuum or a wet method to reduce dust during clean-up. DO NOT DRY SWEEP.
- ▶ Use a high efficiency particulate air (HEPA) filter when vacuuming. Do not use a standard shop vacuum.

## Personal Protective Equipment

The OSHA Personal Protective Equipment Standard (29 CFR 1910.132) requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

### Gloves and Clothing

- ▶ Avoid skin contact with **Cacodylic Acid**. Wear personal protective equipment made from material that can not be permeated or degraded by this substance. Safety equipment suppliers and manufacturers can provide recommendations on the most protective glove and clothing material for your operation.
- ▶ Safety equipment manufacturers recommend Nitrile and Natural Rubber for gloves and DuPont Tyvek®, or the equivalent, as protective materials for clothing.
- ▶ All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.

### Eye Protection

- ▶ Wear eye protection with side shields or goggles.
- ▶ Wear a face shield along with goggles when working with corrosive, highly irritating or toxic substances.

### Respiratory Protection

**Improper use of respirators is dangerous.** Respirators should only be used if the employer has implemented a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing, and medical exams, as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134).

- ▶ For field applications check with your supervisor and your safety equipment supplier regarding the appropriate respiratory equipment.
- ▶ Where the potential exists for exposure under **0.5 mg/m<sup>3</sup>** (as *Arsenic*), use a NIOSH approved negative pressure, air purifying, particulate filter respirator. The filter classifications of dust/mist/fume, paint spray or pesticide prefilters, and filters for radon daughters, have been replaced with the N, R, and P series. Each series has three levels of filtering efficiency: 95%, 99%, and 99.9%.
- ▶ Where the potential exists for exposure over **0.5 mg/m<sup>3</sup>** (as *Arsenic*), use a NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus operated in a pressure-demand or other positive-pressure mode.

## Fire Hazards

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA Fire Brigades Standard (29 CFR 1910.156).

- ▶ Extinguish fire using an agent suitable for type of surrounding fire. **Cacodylic Acid** itself does not burn.
- ▶ POISONOUS GASES ARE PRODUCED IN FIRE, including *Arsenic Oxides*.
- ▶ Use water spray to keep fire-exposed containers cool.

## Spills and Emergencies

If employees are required to clean-up spills, they must be properly trained and equipped. The OSHA Hazardous Waste Operations and Emergency Response Standard (29 CFR 1910.120) may apply.

If **Cacodylic Acid** is spilled, take the following steps:

- ▶ Evacuate personnel and secure and control entrance to the area.
- ▶ Eliminate all ignition sources.
- ▶ Moisten spilled material first or use a HEPA-filter vacuum for clean-up and deposit in sealed containers.
- ▶ Ventilate and wash area after clean-up is complete.
- ▶ DO NOT wash into sewer.
- ▶ It may be necessary to contain and dispose of **Cacodylic Acid** as a HAZARDOUS WASTE. Contact your state Department of Environmental Protection (DEP) or your regional office of the federal Environmental Protection Agency (EPA) for specific recommendations.

## Handling and Storage

Prior to working with **Cacodylic Acid** you should be trained on its proper handling and storage.

- ▶ A regulated, marked area should be established where **Cacodylic Acid** is handled, used, or stored.
- ▶ **Cacodylic Acid** is not compatible with OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE); REDUCING AGENTS (such as LITHIUM, SODIUM, ALUMINUM and their HYDRIDES); STRONG ACIDS (such as HYDROCHLORIC, SULFURIC and NITRIC); CHEMICALLY ACTIVE METALS (such as POTASSIUM, MAGNESIUM and ZINC); and SODIUM BOROHYDRIDE.
- ▶ Store in tightly closed containers in a cool, well-ventilated area away from WATER and MOISTURE as **Cacodylic Acid** absorbs water from the air.

## Occupational Health Information Resources

The New Jersey Department of Health offers multiple services in occupational health. These services include providing informational resources, educational materials, public presentations, and industrial hygiene and medical investigations and evaluations.

### For more information, please contact:

New Jersey Department of Health  
Right to Know  
PO Box 368  
Trenton, NJ 08625-0368  
Phone: 609-984-2202  
Fax: 609-984-7407  
E-mail: [rtk@doh.state.nj.us](mailto:rtk@doh.state.nj.us)  
Web address: <http://www.nj.gov/health/eoh/rtkweb>

*The Right to Know Hazardous Substance Fact Sheets  
are not intended to be copied and sold  
for commercial purposes.*

## GLOSSARY

**ACGIH** is the American Conference of Governmental Industrial Hygienists. They publish guidelines called Threshold Limit Values (TLVs) for exposure to workplace chemicals.

**Acute Exposure Guideline Levels (AEGs)** are established by the EPA. They describe the risk to humans resulting from once-in-a-lifetime, or rare, exposure to airborne chemicals.

**Boiling point** is the temperature at which a substance can change its physical state from a liquid to a gas.

A **carcinogen** is a substance that causes cancer.

The **CAS number** is unique, identifying number, assigned by the Chemical Abstracts Service, to a specific chemical.

**CFR** is the Code of Federal Regulations, which are the regulations of the United States government.

A **combustible** substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes destruction of human skin or severe corrosion of containers.

**DEP** is the New Jersey Department of Environmental Protection.

**DOT** is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

**EPA** is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

**ERG** is the Emergency Response Guidebook. It is a guide for emergency responders for transportation emergencies involving hazardous substances.

**Emergency Response Planning Guideline (ERPG)** values are intended to provide estimates of concentration ranges where one reasonably might anticipate observing adverse effects.

A **fetus** is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

**IARC** is the International Agency for Research on Cancer, a scientific group.

**Ionization Potential** is the amount of energy needed to remove an electron from an atom or molecule. It is measured in electron volts.

**IRIS** is the Integrated Risk Information System database maintained by federal EPA. The database contains information on human health effects that may result from exposure to various chemicals in the environment.

**LEL or Lower Explosive Limit**, is the lowest concentration of a combustible substance (gas or vapor) in the air capable of continuing an explosion.

**mg/m<sup>3</sup>** means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

**NFPA** is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

**NIOSH** is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

**NTP** is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

**OSHA** is the federal Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

**PEOSHA** is the New Jersey Public Employees Occupational Safety and Health Act, which adopts and enforces health and safety standards in public workplaces.

**Permeated** is the movement of chemicals through protective materials.

**PIH** is a DOT designation for chemicals which are Poison Inhalation Hazards.

**ppm** means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

**STEL** is a Short Term Exposure Limit which is usually a 15-minute exposure that should not be exceeded at any time during a work day.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

**UEL or Upper Explosive Limit** is the highest concentration in air above which there is too much fuel (gas or vapor) to begin a reaction or explosion.

**Vapor Density** is the ratio of the weight of a given volume of one gas to the weight of another (usually *Hydrogen*), at the same temperature and pressure.

The **vapor pressure** is a measure of how readily a liquid or a solid mixes with air at its surface. A higher vapor pressure indicates a higher concentration of the substance in air and therefore increases the likelihood of breathing it in.

Common Name: **CACODYLIC ACID**

Synonyms: Hydroxydimethylarsine Oxide

CAS No: 75-60-5

 Molecular Formula: C<sub>2</sub>H<sub>7</sub>AsO<sub>2</sub>

RTK Substance No: 0304

Description: Colorless to white, odorless, crystalline solid

**HAZARD DATA**

Hazard Rating	Firefighting	Reactivity
<b>4 - Health</b> <b>0 - Fire</b> <b>0 - Reactivity</b> DOT#: UN 1572 ERG Guide #: 151 Hazard Class: 6.1 (Poison)	Extinguish fire using an agent suitable for type of surrounding fire. <b>Cacodylic Acid</b> itself does not burn. POISONOUS GASES ARE PRODUCED IN FIRE, including <i>Arsenic Oxides</i> . Use water spray to keep fire-exposed containers cool.	<b>Cacodylic Acid</b> is not compatible with OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE); REDUCING AGENTS (such as LITHIUM, SODIUM, ALUMINUM and their HYDRIDES); STRONG ACIDS (such as HYDROCHLORIC, SULFURIC and NITRIC); CHEMICALLY ACTIVE METALS (such as POTASSIUM, MAGNESIUM and ZINC); and SODIUM BOROHYDRIDE.

**SPILL/LEAKS**
**Isolation Distance:**

Spill: 25 meters (75 feet)

Fire: 800 meters (1/2 mile)

Moisten spilled material first or use a HEPA-filter vacuum for clean-up and deposit in sealed containers.

DO NOT wash into sewer.

Harmful to aquatic life.

**PHYSICAL PROPERTIES**

<b>Odor Threshold:</b>	Odorless
<b>Flash Point:</b>	Nonflammable
<b>Specific Gravity:</b>	>1.2 (water = 1)
<b>Water Solubility:</b>	Soluble
<b>Boiling Point:</b>	392°F (200°C)
<b>Melting Point:</b>	383° to 392°F (195° to 200°C)
<b>Molecular Weight:</b>	138
<b>pH:</b>	Acidic

**EXPOSURE LIMITS**
**OSHA:** 0.5 mg/m<sup>3</sup>, 8-hr TWA (as *Arsenic*)

**NIOSH:** None

**ACGIH:** None

**IDLH:** None

**PROTECTIVE EQUIPMENT**

<b>Gloves:</b>	Nitrile and Natural Rubber
<b>Coveralls:</b>	DuPont Tyvek®
<b>Respirator:</b>	<0.5 mg/m <sup>3</sup> - Full facepiece APR with High efficiency filter >0.5 mg/m <sup>3</sup> - Supplied air

**HEALTH EFFECTS**

<b>Eyes:</b>	Irritation, burns, red and watery eyes
<b>Skin:</b>	Irritation, burns, itching, rash and loss of pigment
<b>Inhalation:</b>	Nose and throat irritation with coughing, wheezing, and hoarseness Weakness, nausea, vomiting, headache and muscle cramps
<b>Chronic:</b>	<i>Arsenic</i> and <i>Arsenic compounds</i> cause bladder, lung, and skin cancer in humans.

**FIRST AID AND DECONTAMINATION**

**Remove** the person from exposure.

**Flush** eyes with large amounts of water for at least 15 minutes. Remove contact lenses if worn. Seek medical attention.

**Quickly** remove contaminated clothing and wash contaminated skin with large amounts of water.

**Begin** artificial respiration if breathing has stopped and CPR if necessary.

**Transfer** promptly to a medical facility.