## DEPARTMENT OF LABOR AND WORKFORCE DEVELOPMENT DIVISION OF PUBLIC SAFETY AND OCCUPATIONAL SAFETY & HEALTH BUREAU OF BOILER AND PRESSURE VESSEL COMPLIANCE 1 JOHN FITCH WAY 3<sup>rd</sup> Floor

1 JOHN FITCH WAY 3<sup>rd</sup> Floor P.O. BOX 392 TRENTON, NJ 08625-0392

Telephone: (609) 292-2345 Email: BPVRCompliance@dol.nj.gov

## INSTALLER/SERVICE VERIFICATION OF FUNCTION TESTING AND OPERATION OF CONTROLS AND SAFETY DEVICES FOR ALL BOILERS

Unit Manufacturer				
Name:				
Address:			Zip Code:	
Telephone:		Fax No:		
Unit Identification (Boiler)				
Manufacturer's Model #ASME Section:			Ye	
FM/UL # Jurisdiction #			County	
Junisdiction #	ividi iicipality		County	
Steam		Hot Water		
Max. W.P.	Psig	Max. W.P		Psig
Min. Safety Valve Cap	PPH	Max. Temp.		°F
		Min. Safety Relief Cap	acity	Ibs/hr. or Btu
Boiler Unit Description (Type)				
f Modular (No. of Modules)				
Boiler Unit Capacity (Output)				
. , , , ,				
Burner				
Manufacturer		Model		
JL or AGA#		Serial #		
Burner Input Capacity		Fuels (as Shipped	)	
		Indicate U	nits (Where applicable, indica	te "N/A")
Gas Manifold Pressure				
Oil Nozzle/Delivery Pressure (at Max input)				
High Gas Pressure Switch Setting				
Low Oil Pressure Switch Setting				
nstallation Location				
Owner Name			Email Address	
Owner Address				
CityZIP	Location of Inst	allation		
Fax (	)	Contact	E-mail	

Rev 3.2016 BPVC-INST.101

Confroi/Device	Ma	nutacturer	Model No.#	Performed Indicate Date
Operating Controls Low-Water Fuel Cutoff CW-120(a), CW-140				
Forced Circulation CW-210(a)				
Steam Pressure CW-310(b)				
Water Temperature CW-410(b)				
Safety Controls Low-Water Fuel Cutoff CW-120(a), CW-120(b) CW-130, CW-140				
Forced Circulation CW-210(b)				_
High Steam Pressure Limit CW-310(c)				
High Water Temperature Limit CW-310(c)				
Fuel Safety Shutoff Valve, Main CF-180(b)(2), CF-180(b)(3)				
Pilot Safety Shutoff Valve CF-180(c)				_
Atomizing Medium Switch CF-450(b)				
Combustion Air Switch CF-220				
High Gas Pressure CF-162				
Low Gas Pressure CF-162				
Low Oil Pressure CF-450(a)				
High Oil Temperature CF-450(c)				_
Low Oil Temperature CF-450(d)				_
Purge Air Flow CF-210				
Flame Safeguard (Primary) CF-310, CF-320				
Flame Detector CF-310, CF-320				
Low Fire Start Low-Fire Start Switch CF-610				
Over-Pressure Protection Safety or Safety Relief Valve(s)				
CW-510, CW-520 Symbol Stamp on Valve	"V" "HV" "UV" Circle what applies		_	
		uards may be required fo	or boilers with a rating of 12.5 r	million Btu/hr or greater per NFPA 85
Representing Equipment Manufacturer		EIN No	<u></u>	
Company Name:		Address:		Tel:
City:	State:	Zip Code:	Email Address:	
Print Name:				Date:
Representing Installing Contractor		EIN No.		T.
Company Name:				
City:	State:	Zip Code:	Email Address:	
Print Name:	§	Signature:		Date:

INSTALLER – RETURN THIS DOCUMENT TO THE ADDRESS INDICATED ON THE FRONT SIDE OR EMAIL COMPLETED FORM TO BPVRCompliance@dol.state.nj.us